### DETOOLZ SMART WORK

SMART Equipments! So you work like a PRO!

micul-fermier.ro

### DETOOLZ SMART WORK

CONTENT

Single platform equipment for batteries FLEXI POWER ...... page 4

Pumps, motor pumps, irrigation and spraying systems ...... page 10

Generators and motors ..... page 15

Chainsaws, electric saws ...... page 16

Earth augers, brush cutters, trimmers ...... page 18

Scissors and gardening tools ..... page 22

Vehicle and bicycle maintenance ...... page 23

Home and camping ......page 24

DIY Products ..... page 34

The information contained in this brochure is of a general presentation and may contain errors due to processing or subsequent changes by the manufacturers. Pictures may not reflect the final shape or color of the product. All products comply with current EC regulations and are available through the GOLDEN FISH SRL distribution network.



### **DZ-SE181**

### **45NM CORDLESS BRUSHLESS** IMPACT DRILL. PERFORMANCE

\*Optimum efficiency by using a battery with a capacity of minumum 2Ah and a voltage of 18V. \*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger D7-SF205

DZ-SE206, DZ-SE207.

\*The product does NOT contain a battery and charger, they are purchased separately.

### **DZ-SE182**

### SDS ROTARY HAMMER 18V **BRUSHLESS, PERFORMANCE**

\*Optimum efficiency by using a battery with a capacity of minumum 4Ah and a voltage of 18V. \*Compatible with battery DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207.

\*The product does NOT contain a battery and charger, they are purchased separately.

### **DZ-SE183**

### CORDLESS BRUSHLESS RECIPROCATING SAW 18V BRUSHLESS 100MM, PERFORMANCE

\*Optimum efficiency by using a battery with a capacity of minumum 4Ah and a voltage of 18V. \*Compatible with battery DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207.

\*The product does NOT contain a battery and charger, they are purchased separately

| Hole diameter:     | wood - 34 mm;                  |
|--------------------|--------------------------------|
|                    | metal - 16 mm;                 |
|                    | brick - 10 mm;                 |
| Impact rate:       | 0-28800 bpm                    |
| Speed:             | Speed I: 0-500 rpm             |
|                    | Speed II: 0-1800 rpm           |
| Max. torque:       | 45 Nm                          |
| Chuck type:        | Automatic                      |
|                    | 1/2" (13mm)                    |
| Engine:            | Brushless                      |
| Operating method:  | screwing, drilling, percussior |
| Adjustment steps:  | 19 steps                       |
| LED working light: | Yes                            |

| Maximum drilling diameter:    | beton: 22 mm;   |
|-------------------------------|-----------------|
|                               | metal: 13 mm;   |
|                               | wood: 28 mm;    |
| Impact rate:                  | 0-4500 bpm      |
| Maximum speed:                | 0-1400 rpm      |
| Battery:                      | 18 V            |
| Rated drilling range:         | 6-12 mm         |
| Chuck type:                   | SDS+            |
| Engine:                       | Brushless motor |
| LED working light:            | Yes             |
| Hammer power:                 | 1.7 J           |
| Depth adjustment limiter:     | Yes             |
| Forward and reverse function: | Yes             |
| Electronic speed regulation:  | Yes             |

| Cutting thickness:         | wood - 200 mm;  |
|----------------------------|-----------------|
|                            | metal - 50 mm;  |
| Maximum speed:             | 0-3000 rpm      |
| Battery:                   | 18 V            |
| Stroke length:             | 28 mm           |
| Quick change blade system: | Yes             |
| Pendulum steps:            | 2 trepte        |
| Engine:                    | Brushless motor |





### **DZ-SE184**

### **CORDLESS ANGLE GRINDER Ø125 18V BRUSHLESS, PERFORMANCE**

\*Optimum efficiency by using a battery with a capacity of minumum 4Ah and a voltage of 18V. \*Compatible with battery DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207.

\*The product does NOT contain a battery and charger, they are purchased separately.

| Maximum speed:  | 8500 rpm        |
|-----------------|-----------------|
| Battery:        | DC 18 V         |
| Spindle thread: | M14             |
| Disc diameter:  | 125 mm          |
| Engine:         | Brushless motor |
| Bore:           | 22.2 mm         |



Single platform equipment for batteries FLEXI POWER



### **DZ-SE185**

### CORDLESS CIRCULAR SAW Ø165MM **18V BRUSHLESS, PERFORMANCE**

\*Optimum efficiency by using a battery with a capacity of minumum 4Ah and a voltage of 18V. \*Compatible with battery DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207.

\*The product does NOT contain a battery and charger, they are purchased separately.

| ٨ | Maximum speed:     | 3650 rpm                  |
|---|--------------------|---------------------------|
| ~ | Battery:           | 18 V                      |
|   | Disc diameter:     | 165 mm                    |
|   |                    | 50 mm at an angle of 90°; |
|   | Cutting depth:     | 35 mm at an angle of 45°; |
|   | Engine:            | Brushless motor           |
|   | Bore:              | 16 mm                     |
|   | Aspirator adapter: | Da                        |
|   | Electronic brake:  | Da                        |
|   | Blade angle        | 45                        |



### **DZ-SE186**

CORDLESS DRILL, 28NM 18V LI-ION

\*Optimum efficiency by using a battery with a capacity of minumum 2Ah and a voltage of 18V.

\*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207.

\*The product does NOT contain a battery and charger, they are purchased separately

| Speed:                     | Speed I: 0-350 rpm;  |
|----------------------------|----------------------|
|                            | Speed II: 0-1150 rpm |
| Max. torque:               | 28 Nm                |
| Battery:                   | DC 18 V              |
| Number of gears:           | 2 gears              |
| Chuck type:                | 3/8" Rapid/Automatic |
| Engine:                    | Brushes              |
| Adjustable torque settings | 19 trepte            |
| Operating method:          | screwing, drilling   |

metal - 10 mm;

matic of

### **DZ-SE187**

### CORDLESS IMPACT DRILL 28NM 18V LI-ION

\*Optimum efficiency by using a battery with a capacity of minumum 2Ah and a voltage of 18V. \*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207.

\*The product does NOT contain a battery and charger, they are purchased separately.

### **DZ-SE188**

### CORDLESS IMPACT DRILL 35NM 18V LI-ION

\*Optimum efficiency by using a battery with a capacity of minumum 2Ah and a voltage of 18V. \*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207.

\*The product does NOT contain a battery and charger, they are purchased separately.

|   |                             | 0-19200 bpm        |
|---|-----------------------------|--------------------|
|   | Speed:                      | Speed I: 0 ÷ 350;  |
|   |                             | Speed II 0 ÷ 1150  |
| y | Operating method:           | screwing; drilling |
| 1 |                             | percussion;        |
|   | Max. torque:                | 28 Nm              |
|   | Number of gears:            | 2                  |
|   | Chuck type:                 | Chuck rapid/auto   |
|   |                             | 3/8" (10 mm)       |
|   | Engine:                     | Brushes            |
|   | Adjustable torque settings: | 20 steps           |
|   | LED working light:          | Yes                |
|   |                             |                    |

Hole diameter:

nnact rate

| Hole diameter:             | wood - 34 mm; metal - 16 |
|----------------------------|--------------------------|
| Hole diameter:             |                          |
| Impact rate:               | mm; brick - 10 mm        |
|                            | 0-19200 bpm              |
| Speed:                     | Speed I: 0 ÷ 350;        |
|                            | Speed II 0 ÷ 1200        |
| Max. torque:               | 35 Nm                    |
| Number of gears:           | 2                        |
| Chuck type:                | Chuck rapid/automatic of |
|                            | 1/2" (13 mm)             |
| Engine:                    | Brushes                  |
| Adjustable torque settings | 16 steps                 |
| LED working light:         | Yes                      |

| Diamentru maxim gaurire: | wood - 34 mm; metal - 16     |
|--------------------------|------------------------------|
|                          | mm; brick - 10 mm            |
| Impact rate :            | 0-3000 bpm                   |
| Speed:                   | Speed I: 0 ÷ 2000 rpm        |
| Max. torque:             | 150 Nm                       |
| Battery:                 | DC 18 V                      |
| Number of gears:         | 1                            |
| Chuck type:              | Quick release chuck 1/4" hex |
| Engine:                  | Brushes                      |
| LED working light:       | Yes                          |
| Suitable screw type:     |                              |
| - standard screw:        | 5 ÷ 12 mm (3/16 "- 1/2")     |
| - high resistance screw: | 5 ÷ 10 mm (3/16 "- 3/8")     |

| Hole diameter:     | beton: 6 mm;  |
|--------------------|---------------|
|                    | metal: 13 mm; |
|                    | wood: 32 mm   |
| Impact rate:       | 0-4750 bpm    |
| Battery:           | DC 18 V       |
| Maximum speed:     | 0-750 rpm     |
| Chuck type:        | SDS+          |
| Engine:            | Brushes       |
| LED working light: | Yes           |
| Hammer power:      | 1J            |

# <sup>-</sup>m equipment for batteries lle platfor







### **DZ-SE189** CORDLESS IMPACT DRIVER

**150NM 18V LI-ION** 

\*Optimum efficiency by using a battery with a capacity of minumum 2Ah and a voltage of 18V. \*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207.

\*The product does NOT contain a battery and charger, they are purchased separately.

### **DZ-SE190**

### CORDLESS ROTARY HAMMER SDS+18V

\*Optimum efficiency by using a battery with a capacity of minumum 2Ah and a voltage of 18V. \*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207.

\*The product does NOT contain a battery and charger, they are purchased separately.

| C | N |
|---|---|
| C | N |
|   | D |
| ( | N |







ngle platform equipment for batteries

**EXI POWER** 

へつつ







### **DZ-SE191**

### CORDLESS CIRCULAR SAW Ø165MM 18V

\*Optimum efficiency by using a battery with a capacity of minimum 4Ah and a voltage of 18V. \*Compatible with battery DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately.

### **DZ-SE192**

### CORDLESS JIG SAW 18V 60MM

\*Optimum efficiency by using a battery with a capacity of minimum 2Ah and a voltage of 18V. \*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately

### **DZ-SE193**

### RECIPROCATING SAW 18V 100MM

\*Optimum efficiency by using a battery with a capacity of minimum 2Ah and a voltage of 18V. \*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately

### **DZ-SE194**

### CORDLESS TRIANGLE DETAIL SANDER 18V 11000RPM

\*Optimum efficiency by using a battery with a capacity of minimum 2Ah and a voltage of 18V.

\*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately

### **DZ-SE195**

### CORDLESS MULTITOOL 18V 15000RPM

\*Optimum efficiency by using a battery with a capacity of minimum 2Ah and a voltage of 18V.

\*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately

### **DZ-SE196**

### ANGLE GRINDER Ø125 18V

\*Optimum efficiency by using a battery with a capacity of minimum 4Ah and a voltage of 18V.

\*Compatible with battery DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately.

| Maximum speed:     | 3800 rpm                    |
|--------------------|-----------------------------|
| Battery:           | DC 18 V                     |
| Disc diameter:     | 165 mm (6-1/2")             |
| Cutting depth:     | 38 mm at an angle of 90°;   |
|                    | 26 mm at an angle of 45°    |
| Engine:            | Brushes                     |
| Sound level:       | LpA=81.47dB(A); K=3.0dB(A); |
|                    | LWA=90dB(A); K=3.0dB(A)     |
| Bore:              | 16 mm                       |
| Aspirator adapter: | Yes                         |
| Blade angle:       | 50°                         |

| Maximum speed: | 0÷2600 rpm                 |
|----------------|----------------------------|
| Battery:       | DC 18 V                    |
| Stroke length: | 14 mm                      |
| Angle:         | 0°/15°/30°/45°(Unghi lama) |
| Engine:        | Brushes                    |
| Cutitng size:  | wood: 60 mm; metal: 6 mm   |

| Cutting thickness     | wood: 100 mm; metal: 6 mm |
|-----------------------|---------------------------|
| Maximum speed:        | 0÷3000 rpm                |
| Battery               | DC 18V                    |
| Lungime cursa         | 22 mm                     |
| Motor                 | Brushes                   |
| Eliberare rapida lama | Yes                       |

| Maximum speed:     | 11000 rpm     |
|--------------------|---------------|
| Battery:           | DC 18 V       |
| Engine:            | Brushes       |
| Aspirator adapter: | Yes           |
| Pad size:          | 135x135x95 mm |
| Dust box:          | Yes           |

| Maximum speed: | 500÷15000 rpm          |
|----------------|------------------------|
| Battery:       | DC 18 V                |
| Angle:         | 3° (Oscillation angle) |
| Engine         | Brushes                |

| Maximum speed:  | 8000 rpm |
|-----------------|----------|
| Battery:        | DC 18 V  |
| Spindle thread: | M14      |
| Disc diameter:  | 115 mm   |
| Engine:         | Brushes  |
| Bore:           | 22 mm    |



### DZ-SE197

### CORDLESS VACUUM CLEANER 600ML 18V WITH EXTENSION AND BRUSH

\*Optimum efficiency by using a battery with a capacity of minimum 2Ah and a voltage of 18V. \*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately

### DZ-SE198

### CORDLESS WORK LIGHT 18V 2400LM COLD LIGHT

\*Optimum efficiency by using a battery with a capacity of minimum 2Ah and a voltage of 18V. \*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately

### DZ-SE199

### CORDLESS BLOWER 210KM/HOUR 18V

\*Optimum efficiency by using a battery with a capacity of minimum 2Ah and a voltage of 18V. \*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately

### **DZ-SE208**

### CORDLESS LEAF VACUUM BLOWER 40L 210KM/HOUR 18V

\*Optimum efficiency by using a battery with a capacity of minimum 4Ah and a voltage of 18V. \*Compatible with battery DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately.

### DZ-SE200

### CORDLESS CHAIN SAW 10" 18V

\*Optimum efficiency by using a battery with a capacity of minimum 4Ah and a voltage of 18V. \*Compatible with battery DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately.

### **DZ-SE201**

### CORDLESS CHAIN SAW 14" 2X18V

\*Optimum efficiency by using a battery with a capacity of minimum 4Ah and a voltage of 18V. \*Compatible with battery DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately.

| Capacity:             | 600 ml            |
|-----------------------|-------------------|
| Net weight:           | 0.9 kg            |
| Engine:               | Brushes           |
| Battery:              | DC 18 V           |
| Tub:                  | Yes               |
| Maximum vacuum power: | 1.8 kPa (18 mbar) |
| Contains:             | extension, brush  |

| Size:               | 27x21x21 cm |
|---------------------|-------------|
| Battery:            | DC 18 V     |
| LED power:          | 24W         |
| Light type:         | Cold        |
| Colour temperature: | 6500K       |
| Power:              | 2400LM      |
| Light source type:  | LED         |

| Battery:            | 1x18 V      |
|---------------------|-------------|
| Net weight:         | 3.5 kg      |
| Air speed:          | 210 km/hour |
| Maximum air volume: | 6 mc/min    |

| Battery:               | 2x18 V      |
|------------------------|-------------|
| Air speed:             | 210 km/hour |
| Maximum air volume:    | 10mc/min    |
| Capacity of catch bag: | 40L         |
| Collecting device:     | Catch bag   |

| Battery:              | DC 18 V           |
|-----------------------|-------------------|
| Chain:                | Oregon            |
| Blade length:         | 254 mm ( 10 inch) |
| Working blade length: | 230 mm (8 inch)   |
| Chain speed:          | 6 m/s             |
| Oil tank capacity:    | 150 ml            |
| Chain pitch:          | 0,325             |
| Chain teeth           | 20                |
| Spur chain:           | 40                |

| Battery:              | DC 2x18 V (36V) |
|-----------------------|-----------------|
| Lama:                 | Oregon          |
| Blade length:         | 355mm (14 inch) |
| Working blade length: | 305mm (12 inch) |
| Chain speed:          | 8.5 m/s         |
| Oil tank capacity:    | 150 ml          |
| Chain pitch:          | 0.325           |
| Chain teeth:          | 26              |
| Spur chain:           | 52              |

# Single platform equipment for batteries FLEXI POWER

20 Contraction 90









TRIMMER 18V, 250MM

\*Optimum efficiency by using a battery with a capacity of minimum 2Ah and a voltage of 18V. \*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately

### DZ-SE226

### CORDLESS RECIPROCATING SAW 18V 28MM

\*Optimum efficiency by using a battery with a capacity of minimum 4Ah and a voltage of 18V. \*Compatible with battery DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately.

### **DZ-SE227**

### EXTENSION BAR FOR DZ-SE226

Extension bar for the chain of the chain saw and battery, 18V, 2Ah, Detoolz DZ-SE147.

### DZ-SE228

CORDLESS LAWN MOWER, 18V, 320MM, 25L

\*Optimum efficiency by using a battery with a capacity of minimum 4Ah and a voltage of 18V. \*Compatible with battery DZ-SE203, DZ-SE204 and charger DZ-SE205,

DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately.

### **DZ-SE229**

### CORDLESS LAWN MOWER, 2X18V, 380MM, 36L

\*Optimum efficiency by using a battery with a capacity of minimum 2Ah and a voltage of 18V.

\*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately

| Maximum speed:           | 8500 rpm                |
|--------------------------|-------------------------|
| Line diameter:           | 1.2mm x 5m              |
| Trimmer features         | Feature EDGE            |
|                          | - With trimming well    |
| Length standard axis and | 90 cm                   |
| telescopic:              |                         |
| Telescopic length:       | 300 mm                  |
| Trimmer cutting device:  | - nylon cutting;        |
|                          | - plastic blade cutting |
| Engine:                  | Brushes                 |
| Battery:                 | 18 V                    |
|                          |                         |

| Product type:       | Reciprocating saw        |
|---------------------|--------------------------|
| Cutting thickness : | wood: 28 mm; metal: 3 mm |
| Maximum speed:      | 0 - 2200 rpm             |
| Battery:            | 18 V                     |
| Stroke length:      | 14 mm                    |
| Number of gears:    | 1                        |
| Engine:             | Brushes                  |
| Tightness class:    | IP20                     |

| Product type  | Extension bar      |
|---------------|--------------------|
| Extension arm | Yes (for DZ-SE226) |
| Arm length    | 1.2m               |

| Maximum speed:            | 2900 rpm                  |
|---------------------------|---------------------------|
| Net weight:               | 8.5 kg                    |
| Cutting width:            | 320 mm                    |
| Brake lever control:      | Yes                       |
| Wheel size:               | R 13.5 cm                 |
| Engine:                   | Brushes                   |
| Foldable handle:          | Yes                       |
| Adjustable cutting height | 3 trepte: 25/40/55 mm     |
| Cutting height:           | 25 - 45 mm with 3 degrees |
|                           |                           |

|                           | 2700                        |
|---------------------------|-----------------------------|
| Maximum speed:            | 3700 rpm                    |
| Net weight:               | 15.5 kg                     |
| Cutting width:            | 380 mm                      |
| Brake lever control:      | Yes                         |
| Wheel size:               | R 15.5 cm                   |
| Engine:                   | Brushes                     |
| Battery:                  | 2 x 18 V (36 V)             |
| Bridge size:              | 75 x 45 x 31 cm             |
| Foldable handle:          | Yes                         |
| Adjustable cutting height | 5 trepte: 25/35/45/55/65 mm |
| Cutting height:           | 25 - 75 mm cu 5 grade       |
| Height adjustment wheels: | Yes (individual)            |
| Grass bag capacity:       | 36 I                        |





### **DZ-SE230**

### CORDLESS SPRAYER, 18V 600ML/ MIN TANK 1000ML

\*Optimum efficiency by using a battery with a capacity of minimum 2Ah and a voltage of 18V. \*Compatible with battery DZ-SE202, DZ-SE203, DZ-SE204 and charger DZ-SE205, DZ-SE206, DZ-SE207

\*The product does NOT contain a battery and charger, they are purchased separately

| Flow rate (ml/min): | 600 ml/min             |
|---------------------|------------------------|
| Tank capacity:      | 1000 ml                |
| Battery:            | 18 V                   |
| Maximum viscosity:  | 80 Din-s               |
| Nozzle diameter:    | 1.6 mm; 1.8 mm; 2.2 mm |



### **DZ-SE202**

UNIVERSAL BATTERY 18V/2AH

Battery type Li-Ion Battery 18 V

### Battery type: Li-Ion

Charging time with charger DZSE205: 55 minutes Charging time with charger DZSE206: 33 minutes Charging time with charger DZSE207: 37 minutes



### **DZ-SE203**

UNIVERSAL BATTERY 18V/4AH Battery type Li-lon Battery 18 V

### Battery type: Li-Ion Battery: 18 V Charging time with charger DZSE205: 100 minutes Charging time with charger DZSE206: 66 minutes Charging time with charger DZSE207: 75 minutes



### **DZ-SE204**

UNIVERSAL BATTERY 18V/6AH Battery type Li-Ion Battery 18 V New technology cells 21700

### Battery type: Li-Ion Charging time with charger DZSE205: 165 minutes Charging time with charger DZSE206: 99 minutes Charging time with charger DZSE207: 113 minutes



**DZ-SE205** CHARGER 1 BATTERY 18V **CHARGING 2.4A/HOUR** 

Battery type Li-lon Charger 1 battery 18 V

### Battery type: Li-Ion Charging time for battery DZ-SE202: 55 minutes Charging time for battery DZ-SE203: 100 minutes Charging time for battery DZ-SE204: 165 minutes



### **DZ-SE206** CHARGER 1 BATTERY 18V

**CHARGING 4A/HOUR** 

Battery type Li-Ion Charger 1 battery 18 V

### Battery type: Li-Ion

Output voltage: 14.4-18V DC Charging time for battery DZ-SE202: 33 minutes Charging time for battery: DZ-SE204 99 minutes



### **DZ-SE207**

**CHARGER 2 BATTERIES 18V CHARGING 3.5A/HOUR** 

9

Battery type Li-Ion Charger 2 battery 18 V

### Battery type: Li-Ion

Output power: 3.5A Charging time for battery DZ-SE202: 37 minutes Charging time for battery DZ-SE204: 113 minutes



### DZ-P103-S001-G01

WATER BOOSTER SYSTEM 0,75KW/1HP AUJET 100SS, COPPER COILING

Product type: Water booster system

| Power kW/W:        | 0.75 kW |
|--------------------|---------|
| Max. intake depth: | 9 m     |
| Displacement:      | 1.01 HP |
| Tank capacity:     | 241     |
| Discharge height:  | 45 m    |



Pumps, motor pumps, irrigation



DZ-P104-S001-G01

WATER BOOSTER SYSTEM 0,75KW/1HP AUJET 100L, COPPER COILING

Product type: Water booster system

| Power kW/W:             | 0.75 kW/01 HP |
|-------------------------|---------------|
| Maximum discharge flow: | 3.9 m³/h      |
| Max. intake depth:      | 9 m           |
| Displacement:           | 1.01 HP       |
| Tank capacity:          | 24            |
| Discharge height:       | 42 m          |



### **DZ-P122**

WATER BOOSTER SYSTEM 0,75KW/1HP AUJET-100B 50L Water booster system. New product!

| Maximum flow:               | 55 l/min     |
|-----------------------------|--------------|
| Maximum speed:              | 2850 rpm     |
| Max. intake depth:          | 9 m          |
| Inaltime totala de pompare: | 45 m         |
| Liquid max. temperature:    | 35°C         |
| Tank capacity:              | 50           |
| Diametru Connection:        | 1"           |
| Shaft material:             | Carbon steel |
| Rotor blade material:       | Alama        |
| Power kW/W:                 | 0.75 kW      |

## 2022



### DZ-P123

WATER BOOSTER SYSTEM 0,75KW/1HP AUJS-100 50L Product type: Water booster system. New product!

| Maximum temperature: | 35 °C  |
|----------------------|--------|
| Maximum depth:       | 7 m    |
| Maximum height:      | 8,5 m  |
| Power kW/W:          | 0.75 W |
| Power HP:            | 1 HP   |



### DZ-P105-S001-G01 SURFACE WATER PUMP 0,75KW/1HP JET 100SS

Product type: Surface water pump. New product!

| Power kW/HP:              | 0.75 kW/ 1 HP   |
|---------------------------|-----------------|
| Maximum speed:            | 2850 rpm        |
| Intake depth:             | 9 m             |
| Maximum discharge flow:   | 55 l/min        |
| Pumping height:           | 45 m            |
| Coiling:                  | Copper          |
| Pump shaft material:      | Stainless steel |
| Pump body material:       | Stainless steel |
| Max. working temperature: | 35°C            |



### DZ-P106-S001-G01 SURFACE WATER PUMP

0,75KW/1HP JET 100L

Product type: Surface water pump. New product!

| Power kW/HP:            | 0.75 kW/ 1 HP |
|-------------------------|---------------|
| Maximum speed:          | 2852 rpm      |
| Intake depth:           | 9 m           |
| Maximum discharge flow: | 65 l/min      |
| Pumping height:         | 42 m          |
| Coiling:                | Copper        |
| Shaft material:         | Carbon steel  |
| Body material:          | Fonta         |
| Maximum temperature:    | 35 °C         |



### DZ-P117 DEEP WELL PUMP 55M 6 BAR 1000W 5200 L/H

Product type: Vibration pump.

| Power kW/W:              | 1000 W              |
|--------------------------|---------------------|
| Flow:                    | 5200 l/h            |
| Discharge height:        | 55 m                |
| Maximum working height:  | 79 cm               |
| Maximum pressure:        | 6 bar               |
| Maximum speed:           | 2900 rpm            |
| Intake maximum height:   | 16 m                |
| Liquid max. temperature: | 35 °C               |
| Pump body material:      | Stainless steel 301 |
| Drive shaft material:    | Stainless steel 420 |



### DZ-P118 DEEP WELL PUMP

55M 5.5 BAR 1000W 5200 L/H Product type: Vibration pump.

| Power kW/W:              | 1000 W              |
|--------------------------|---------------------|
| Flow:                    | 5200 l/h            |
| Discharge height:        | 55 m                |
| Maximum working height:  | 69 cm               |
| Maximum pressure:        | 5.5 bar             |
| Maximum speed:           | 2900 rpm            |
| Intake maximum height:   | 16 m                |
| Liquid max. temperature: | 35 °C               |
| Pump body material:      | Stainless steel 301 |
| Drive shaft material:    | Stainless steel 420 |



### DZ-P100

CLEAN/DIRTY WATER SUBMERSIBLE PUMP 3IN1 400W

Product type: Domestic water pump without chipper, with float

| Power kW/HP:         | 0.4 kW/0.54 HP |
|----------------------|----------------|
| Maximum depth:       | 7 m            |
| Maximum flow:        | 11 m³/h        |
| Maximum height:      | 6 m            |
| Discharge diameter:  | 1.1/4 inch     |
| Maximum temperature: | 35 °C          |



### **DZ-P101**

CLEAN/DIRTY WATER SUBMERSIBLE PUMP 3IN1 500W

Product type: Domestic water pump without chipper, with float

| Power kW/HP:         | 0.5 kW/0.7 HP |
|----------------------|---------------|
| Maximum depth:       | 7 m           |
| Maximum flow:        | 12.5 m³/h     |
| Maximum height:      | 7 m           |
| Discharge diameter:  | 1.1/4 inch    |
| Maximum temperature: | 35 ℃          |



### **DZ-P102**

CLEAN/DIRTY WATER SUBMERSIBLE PUMP 3IN1 750W

Product type: Domestic water pump without chipper, with float

| Power kW/HP:         | 0.75 kW/01 HP |
|----------------------|---------------|
| Maximum depth:       | 7 m           |
| Maximum flow:        | 17.5 m³/h     |
| Maximum height:      | 8.5 m         |
| Discharge diameter:  | 1.1/4 inch    |
| Maximum temperature: | 35 °C         |



### **DZ-P113**

DIRTY WATER PLASTIC PUMP 900W 300L/MIN

Product type: Dirty water pump. New product!

| Max. intake depth: | 7 m       |
|--------------------|-----------|
| Flow:              | 18000 l/h |
| Pumping height:    | 15.9 m    |
| Discharge height:  | 8.9 m     |
| Power kW/W:        | 900 W     |
| Speed:             | 2850 rpm  |
| Connection:        | 1'1/4″    |
| Level float:       | Yes       |

Pumps, motor pumps, irrigation

and spraying systems



### DZ-P114

DIRTY WATER PLASTIC PUMP 750W 217L/MIN

Product type: Dirty water pump. New product!

| Max. intake depth: | 7 m       |
|--------------------|-----------|
| Maximum flow:      | 13500 l/h |
| Pumping height:    | 15 m      |
| Discharge height:  | 8 m       |
| Power kW/W:        | 750 W     |
| Speed:             | 2850 rpm  |
| Connection:        | 1'1/4"    |
| Level float:       | Yes       |



ETOOL

### DZ-P107

SUBMERSIBLE WATER PUMP WQD1500DF 1500W WITH CHIPPER

Product type: Domestic water pump with chipper, with float.

| Power kW/HP:           | 1.5 kW/2 HP |
|------------------------|-------------|
| Maximum depth:         | 7 m         |
| Maximum flow:          | 23 m³/h     |
| Discharge max. height: | 14 m        |
| Discharge diameter:    | 2 inch      |
| Maximum temperature:   | 35°C        |

### DZ-P120

STAINLESS STEEL SUBMERSIBILE PUMP WITH FLOAT 1 000W 6700L/H

Product type: Depth submersible pumps, with float.

| Power kW/W:                    | 1000 W     |
|--------------------------------|------------|
| Maximum depth:                 | 12 m       |
| Maximum flow:                  | 6300 l/h   |
| Discharge height:              | 34 m       |
| Maximum working pressure:      | 3.5 bar    |
| Max. diameter solid particles: | 2-3 mm     |
| Maximum temperature:           | 35 ℃       |
| Pump type:                     | with float |

DEFOOLZ

### DZ-P121

STAINLESS STEEL SUBMERSIBILE 1000W 6700L/H

Product type: Depth submersible pumps, with float.

| 1000 W     |
|------------|
| 12 m       |
| 6300 l/h   |
| 34 m       |
| 3.5 bar    |
| 2-3 mm     |
| 35 °C      |
| with float |
|            |



### DZ-P115

SWIMMING POOL PUMP 600W 11000L/MIN

Product type: Swimming pool pump. New product!

| Power kW/W:                       | 600 W               |
|-----------------------------------|---------------------|
| Maximum flow:                     | 11000 l/h           |
| Discharge max. height:            | 12.5 m              |
| Maximum pressure:                 | 1.25 bar            |
| Maximum working height:           | 23 cm               |
| Maximum speed:                    | 2800 rpm            |
| Drive shaft and coiling material: | Stainless steel 420 |
| Max. working temperature:         | 35 °C               |



### DZ-P116 SWIMMING POOL PUMP 800W 15000L/MIN

Pump type: Swimming pool pump. New product!

| Power kW/W:               | 800 W               |
|---------------------------|---------------------|
| Maximum flow:             | 15000 l/h           |
| Discharge maximum height: | 13.5 m              |
| Maximum pressure:         | 1.35 bar            |
| Min. working height:      | 31 cm               |
| Maximum speed:            | 2800 rpm            |
| Shaft material:           | Stainless steel 420 |
| Coiling:                  | 100% Copper         |
| Max. working temperature: | 35 °C               |



### DZ-P119 SWIMMING POOL PUMP 850W 3150L/H 35M

Product type: Swimming pool pump. New product!

| Power kW/W:                  | 850 W               |
|------------------------------|---------------------|
| Max. intake depth:           | 8 m                 |
| Flow:                        | 3600 l/h            |
| Discharge max. height:       | 38 m                |
| Maximum pressure:            | 3.8 bar             |
| Maximum speed:               | 2800 rpm            |
| Drive shaft material:        | Stainless steel 420 |
| Coiling:                     | 100% Copper         |
| Maximum working temperature: | 35 °C               |







### DZ-P111

### 2L HIGH PRESSURE MANUAL SPRAY PUMP

Pump type: Manual spray pump. New product!

### DZ-P112



Pump type: Manual spray pump. New product!

### **DZ-P108**

### 5L SPRAY PUMP WITH BATTERY

Product type: Spray pump with battery. New product!

| Flow of sprayed liquid:      | 1.0 l/min |
|------------------------------|-----------|
| Working pressure:            | 2.0 MPA   |
| Continuous use time          |           |
| per charge:                  | 2.5 h     |
| Estimation fills per charge: | 20-25     |
| Solution container volume:   | 51        |
| Battery:                     | 2 Ah      |

Solution container volume: 2 I

Solution container volume: 2 I

## DEFOUNDING

### DZ-P109

### SPRAY PUMP WITH BATTERY 16L PRESSURE/LUMBAR SUPPORT

Product type: Spray pump with battery. New product!

| Flow of sprayed liquid:      | 4.0 l/min |
|------------------------------|-----------|
| Working pressure:            | 2.7 MPA   |
| Continuous use time          |           |
| per charge:                  | 5.5 h     |
| Estimation fills per charge: | 30-50     |
| Solution container volume:   | 16 I      |
| Battery:                     | 9 Ah      |

## 2022



### **DZ-P110**

### SPRAY PUMP WITH BATTERY 16L PRESSURE HOSE DZ

Product type: Spray pump with battery. New product!

| Flow of sprayed liquid:      | 4.0 l/min |
|------------------------------|-----------|
| Working pressure:            | 2.7 MPA   |
| Continuous use time          |           |
| per charge:                  | 5.5 h     |
| Estimation fills per charge: | 30-50     |
| Solution container volume:   | 16        |
| Battery:                     | 9 Ah      |



DIGITAL INVERTER GENERATOR 53.5CC 1.75KW GASOLINE

| Fuel:                    | Gasoline              |
|--------------------------|-----------------------|
| Fuel tank                |                       |
| capacity:                | 2.5                   |
| Displacement:            | 53.5 CC               |
| Power:                   | 2.01 HP (heat engine) |
| Power kW/W:              | 1.5 kW (heat engine)  |
| Output/input max. power: | 1000 W / 1100 W       |
| Speed at rated power:    | 4500 rpm              |
| Maximum speed:           | 5000 rpm              |
| Continuous operation:    | 3.5 h                 |
| Rated charge:            | 6 h - 1/4 charge      |
| Fuel consumption:        | 360 g/kW/h            |
| Starting system:         | Rope start            |
| Ignition system:         | TCI                   |
| Functions:               | USB                   |



### DZ-C261

DIGITAL INVERTER GENERATOR 79.5CC 2.75KW GASOLINE

| Fuel:                    | Gasoline              |
|--------------------------|-----------------------|
| Fuel tank                |                       |
| capacity:                | 41                    |
| Displacement:            | 79.5 CC               |
| Power::                  | 3.22 HP (heat engine) |
| Power kW/W:              | 2.4 kW (heat engine)  |
| Output/input max. power: | 2000 W / 2100 W       |
| Speed at rated power:    | 5000 rpm              |
| Maximum speed:           | 5500 rpm              |
| Continuous operation:    | 3.5 h                 |
| Rated charge:            | 8 h - 1/4 charge      |
| Fuel consumption:        | 360 g/kW/h            |
| Starting system:         | Rope start            |
| Ignition system:         | TCI                   |
| Functions:               | USB                   |

| Fuel:                   | Gasoline                                   |
|-------------------------|--|
| Fuel tank               |  |
| capacity:               | 15 I                                       |
| Displacement:           | 208 CC                                     |
| Power:                  | 7 HP                                       |
| Putere max. de iesire:  | 2.8 kW                                     |
| Speed:                  | 3000 rpm                                   |
| Continuous operation:   | 10 h                                       |
| Fuel consumption:       | 380 g/kW/h                                 |
| Engine oil capacity:    | 0.61                                       |
| Engine oil consumption: | 1.5 g/kW/h                                 |
| Ignition system:        | TCI  |
| Starting system:        | Rope start                                 |
| Functions:              | •Engine shutdown at                        |
|                         | overload/low oil level;                    |
|                         | <ul> <li>Voltage regulator;</li> </ul>     |
|                         | <ul> <li>Low oil level warning;</li> </ul> |
|                         | •Overload sensor.                          |

| Fuel:                   | Gasoline                                   |
|-------------------------|--|
| Fuel tank               |  |
| capacity:               | 25 I                                       |
| Displacement:           | 389 CC                                     |
| Power:                  | 13 HP                                      |
| Putere max. de iesire:  | 5.5 kW                                     |
| Starting power:         | 150 W                                      |
| Speed:                  | 3000 rpm                                   |
| Continuous operation:   | 13 h                                       |
| Fuel consumption:       | 390 g/kW/h                                 |
| Engine oil capacity:    | 1.11                                       |
| Engine oil consumption: | 1.8 g/kW/h                                 |
| Ignition system:        | TCI  |
| Starting system:        | Rope start (demaraj electric               |
| Functions:              | <ul> <li>Engine shutdown at</li> </ul>     |
|                         | overload/low oil level;                    |
|                         | <ul> <li>Voltage regulator;</li> </ul>     |
|                         | <ul> <li>Low oil level warning;</li> </ul> |
|                         | •Overload sensor.                          |

2022



### DZ-C287

GASOLINE GENERATOR 7CP 2.8KW

### DZ-C288

GASOLINE GENERATOR 13CP 5.5KW







### DZ-D101

### ELECTRIC SAW WITH CHAIN 2400W

| Power kW / W:           | 2.4 kW  |
|-------------------------|---------|
| Power HP:               | 3.2 HP  |
| Chain speed:            | 14 m/s  |
| Cutting length:         |         |
| Rail length:            | 16 inch |
| Chain oil tankcapacity: | 280 ml  |
| Frequency:              | 50 Hz   |
| Voltage:                | 220 V   |

### DZ-D102

### ELECTRIC SAW WITH CHAIN 2000W

| Power kW / W:           | 2.0 kW  |
|-------------------------|---------|
| Power HP:               | 2.68 HP |
| Chain speed:            | 13 m/s  |
| Cutting length:         | 395 mm  |
| Rail length:            | 16 inch |
| Chain oil tankcapacity: | 280 ml  |
| Frequency:              | 50 Hz   |
| Voltage:                | 220 V   |

### DZ-D103

ELECTRIC SAW WITH CHAIN 1600W

| Power kW / W:           | 1.6 kW  |
|-------------------------|---------|
| Power HP:               | 2.15 HP |
| Chain speed:            | 13 m/s  |
| Cutting length:         |         |
| Rail length:            | 400 mm  |
| Chain oil tankcapacity: | 280 ml  |
| Frequency:              | 50 Hz   |
| Voltage:                | 230 V   |
|                         |         |

2022



### DZ-D112

GASOLINE CHAINSAW 49.3CC

| Power:         | 2.58 HP, 1.9 kW           |
|----------------|---------------------------|
| Engine:        | 2 stroke, single cylinder |
| Speed:         | 8500 rpm                  |
| Rail length:   | 16 inch                   |
| Tank capacity: | 260 ml (chain oil)        |
| Tank capacity: | 550 ml (fuel)             |
| Engine:        | Euro V                    |
| Chain pitch:   | 0.325                     |
| Guide bar:     | 1.5 mm                    |
| Chain teeth:   | 32                        |
| Spur chain:    | 64                        |



### DZ-D106

CHAIN FOR CHAINSAW 0.325 64 DRIVE LINKS, 32 TEETH, 1.5MM, 16"

| Number of teeth:       | 32     |
|------------------------|--------|
| Number of drive links: | 64     |
| Chain pitch:           | 0.325" |
|                        |        |



### DZ-D104

CHAIN FOR CHAINSAW 25 TEETH, 50 DRIVE LINKS, PITCH PICO 3/8"

| Number of teeth:       | 25         |
|------------------------|------------|
| Number of drive links: |            |
| Chain pitch:           | 3/8" picco |

DZ-D10

DETOOLZ

CHAIN FOR CHAINSAW 3/8LP 50

DRIVE LINKS, 25 TEETH, 1.3MM, 14"

**DZ-D107** 

16

|       | DRUJBA 3 | 2 DINTI. |
|-------|----------|----------|
|       | PAS .325 | NI,<br>7 |
| - The | 0000     | 6000     |
|       | 27       | 2        |
| C C   | 6.0      |          |
|       | 12,      | 2        |
| G     | 0105     |          |

### DZ-D105

CHAIN FOR CHAINSAW 32 TEETH, 64 DRIVE LINKS, PITCH 325"

| Number of teeth:       | 32     |
|------------------------|--------|
| Number of drive links: | 64     |
| Chain pitch:           | 0.325" |



DZ-D108

COMBO PAS3/8LP LAMA 35CM + CHAIN 50 DRIVE LINKS 25 TEETH

| Blade length:          | 35 cm/ 14"           |
|------------------------|----------------------|
| Number of rivets:      |                      |
| Chain type:            | full chisel          |
| Chain pitch:           | 3/8 LP (little pico) |
| Size:                  | 0.50" / 1.3 mm       |
| Number of drive links: |                      |
| Number of teeth:       | 25                   |



### DZ-D109

COMBO PAS.325" BLADE 33CM + CHAIN 56 DRIVE LINKS 28 TEETH

| Blade length:          | 33 cm/ 13"     |
|------------------------|----------------|
| Number of rivets:      | 4              |
| Chain type:            | full chisel    |
| Chain pitch:           | 325"           |
| Size:                  | 0.58" / 1.5 mm |
| Number of drive links: |                |
| Number of teeth:       | 28             |



### **DZ-D110**

COMBO PAS.325" BLADE 38CM + CHAIN 64 DRIVE LINKS 32 TEETH

| Blade length:          | 38 cm/ 15"     |
|------------------------|----------------|
| Number of rivets:      | 4              |
| Chain type:            | full chisel    |
| Chain pitch:           | 325"           |
| Size:                  | 0.58" / 1.5 mm |
| Number of drive links: | 64             |
| Number of teeth:       | 32             |



### DZ-D113

CHAIN FOR CHAINSAW .325" 56 DRIVE LINKS 28 TEETH

| Number of teeth:       | 28          |
|------------------------|-------------|
| Number of drive links: |             |
| Chain pitch:           | 325"        |
| Chain type:            | Full chisel |
| Blade length:          | 35 cm       |



### DZ-D114 CHAIN FOR CHAINSAW 3/8LP 55 DRIVE LINKS 27.5 TEETH

| Number of teeth:       | 27.5                 |
|------------------------|----------------------|
| Number of drive links: | 55                   |
| Chain pitch:           | 3/8 LP (little pico) |
| Chain type:            | Full chisel          |
| Blade length:          | 40 cm                |



DZ-D115

### CHAIN FOR CHAINSAW 3/8LP 52 DRIVE LINKS 26 TEETH

| Number of teeth:       | 26                   |
|------------------------|----------------------|
| Number of drive links: | 52                   |
| Chain pitch:           | 3/8 LP (little pico) |
| Chain type:            |                      |
| Blade length:          | 35 cm                |
|                        | 0.50"/1.3 mm         |



### DZ-D116

CHAIN FOR CHAINSAW .325" 72 DRIVE LINKS 36 TEETH

| Number of teeth:       | 36           |
|------------------------|--------------|
| Number of drive links: | 72           |
| Chain pitch:           | 325"         |
| Chain type:            |              |
| Blade length:          | 45 cm        |
| Size:                  | 0.58"/1.5 mm |

| nm |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |
|    |  |  |  |
|    |  |  |  |
|    |  |  |  |
| ו  |  |  |  |
|    |  |  |  |

2022

DZ-D111 ELECTRIC CHAINSAW SHARPENER 220W

| Size:       | 265x180x205 mm |
|-------------|----------------|
| Frequency : | 50 ÷ 60 Hz     |
| Power kW/W: | 220 W          |
| Tension:    | 220 ÷ 230 V    |
| Speed:      | 7500 rpm       |
| Shaft size: | 10 mm          |
| Disc size:  | 100x10x3.2 mm  |



### DZ-M103

BRUSH CUTTER 4 STROKE BC35T 0.8KW 1.09CP WITH 3 ACCESORIES

Product type: Gasoline brush cutter. New product!

### DZ-M102

GASOLINE BRUSH CUTTER 4T 38.9CC 1.63CP EURO V

Product type: Gasoline brush cutter. New product!

### DZ-M100

GASOLINE BRUSH CUTTER 51.7CC EURO V

Product type: Gasoline brush cutter. New product!

### DZ-M101

ELECTRIC START GASOLINE BRUSH CUTTER 51.7CC EURO V

Product type: Gasoline brush cutter. New product!



### DZ-M121

### GASOLINE BRUSH CUTTER 2T 52CC WITH 4 ACCESORIES

Product type: Gasoline brush cutter. New product!

| Carburator:               | Tip diafragma             |
|---------------------------|---------------------------|
| Fuel:                     | Unleaded petrol           |
| Pipe diameter:            | 26 mm                     |
| Pipe length:              | 1500 mm                   |
| Racire:                   | Cu aer                    |
| Ignition system:          | Electronic                |
| Idling speed:             | 2800-3000 rpm             |
| Turatie motor in sarcina: | 6500 rpm                  |
| Displacement:             | 31 CC                     |
| Fuel tank capacity:       | 700 ml                    |
| Power kW/HP:              | 0.8 kW/1.09 HP            |
| Starting system:          | Manuala                   |
| Engine:                   | 4T, cu un singur cilindru |
| Cutting diameter:         | 225 mm                    |
| Oil tank capacity:        | 70 ml                     |
| Pipe type:                | Fix                       |

| Pipe diameter:    | 26 mm                                |
|-------------------|--------------------------------------|
| Pipe length:      | 1500 mm                              |
| Racire:           | Racire fortata cu aer                |
| Fuel tank:        | 700 ml                               |
| Ignition system:  | тсі                                  |
| Idling speed:     | 2800-3200 rpm                        |
| Displacement:     | 38.9 CC                              |
| Power kW/HP:      | 1.2 kW/1.63 HP                       |
| Carburant:        | Euro V                               |
| Starting system:  | Rope start                           |
| Engine:           | 4 T, single cylinder, OHV air cooled |
| Engine speed:     | 7000 rpm                             |
| Oil tank:         | 70 ml                                |
| Cutting diameter: | 420 mm                               |

| Power kW/HP:      | 1.4 kW/1.9 HP                   |
|-------------------|---------------------------------|
| Fuel:             | Gasoline Euro V                 |
| Pipe diameter:    | 28 mm (double short pipe)       |
| Pipe length:      | 1500 mm                         |
| Fuel tank:        | 1100 ml                         |
| Ignition system:  | TCI                             |
| Engine speed:     | 6500 rpm                        |
| Maximum speed:    | 2800-3200 rpm                   |
| Cutting diameter: | 420 mm                          |
| Displacement:     | 51.7 CC                         |
| Starting system:  | Rope start                      |
| Engine:           | 2T, single cylinder, air cooled |
|                   |                                 |

| Power kW/HP:      | 21.4 kW/1.9 HP                  |
|-------------------|---------------------------------|
| Fuel:             | Gasoline Euro V                 |
| Pipe diameter:    | 28 mm (double short pipe)       |
| Pipe length:      | 1500 mm                         |
| Fuel tank:        | 900 ml                          |
| Ignition system:  | тсі                             |
| Engine speed:     | 6500 rpm                        |
| Maximum speed:    | 2800-3200 rpm                   |
| Cutting diameter: | 420 mm                          |
| Displacement:     | 51.7 CC                         |
| Starting system:  | Rope start and electric         |
| Engine:           | 2T, single cylinder, air cooled |

| Model motor:                 | 2T single cylinder, air |
|------------------------------|-------------------------|
|                              | cooled                  |
| Starting system:             | Rope start              |
| Ignition type:               | TCI                     |
| Diametru cilindru:           | 44 mm                   |
| Power:                       | 1.9 HP / 1.4 kW         |
| Engine speed:                | 6500 RPM                |
| Displacement:                | 52 CC                   |
| Fuel type:                   | Unleaded gasoline       |
| Fuel:                        | Amestec benzina: ulei   |
| Raport amestec benzina:ulei: | 25:1                    |
| Fuel tank:                   | 1200 ml                 |
| Pipe diameter:               | 28 mm                   |
| Pipe length:                 | 1500 mm                 |
| Cutting diameter:            | Lama 255 mm             |
|                              | Cutter nilon 415 mm     |
| Noise silencer:              | Normal silencer         |



### DZ-SE124

ELECTRIC TRIMMER FOR GARDEN 250W

Product type: Electric trimmer. New product!

| Cutting diameter:  | 220 mm      |
|--------------------|-------------|
| Line diameter:     | 1.2 mm      |
| Power kW/W:        | 250 W       |
| Voltage/Frequency: | 220 V/50 Hz |
| Cutting speed:     | 12500 rpm   |



### DZ-SE125

ELECTRIC TRIMMER WITH TELESCOPIC HANDLE 350W

Product type: Electric trimmer. New product!

| Cutting diameter:  | 250 mm      |
|--------------------|-------------|
| Line diameter:     | 1.2 mm      |
| Power kW/W:        | 350 W       |
| Voltage/Frequency: | 220 V/50 Hz |
| Cutting speed:     | 12000 rpm   |



### DZ-SE215 ELECTRIC TRIMMER FOR HEDGES 550W

Product type: Electric trimmer. New product!

| Power kW/W:                  | 550 W             |
|------------------------------|-------------------|
| Engine speed:                | 1700 rpm          |
| Maximum cutting diameter:    | 16 mm             |
| Teeth distance:              | 20 mm             |
| Blade material:              | 65 Mn             |
| Equipment material:          | ABS               |
| Tightness class:             | IP20              |
| Insulation class:            | Double insulation |
| Electrical protection class: | II                |
|                              |                   |



### **DZ-SE224**

CUTTING WIDTH ROBOTIC MOWER 18 CM, BATTERY 2AH 600 MP

Product type: Cutting width robotic mower. New product!

| DC 28 V                      |
|------------------------------|
| 2 Ah                         |
| 1.8 A                        |
| 1.5 h                        |
| Fara perii                   |
| 600 mp                       |
| 100 m                        |
| 150 buc.                     |
| approx. 45 min               |
| 3 pcs. + 6 pcs. as accessory |
| max. 20°                     |
| 20 - 60 mm                   |
| 180 mm                       |
| Linie dreapta si aleatoriu   |
| 0.4 m/s                      |
| 2900 rpm                     |
| Yes                          |
| Yes                          |
| Yes                          |
| IP56                         |
|                              |

DC 29 V

2022

Valtaga



DZ-M104

GASOLINE LAWNMOWER, 16", 146CC, 40L Product type: Lawnmower. New product!



DZ-M105 GASOLINE LAWNMOWER, 17", 146CC, 40L

Product type: Lawnmower. New product!



### DZ-M106

GASOLINE LAWNMOWER, 18", 146CC, 60L

Product type: Lawnmower. New product!



### DZ-M107

GASOLINE LAWNMOWER, 21", 196CC, 70L

20

Product type: Lawnmower. New product!

| Power kW/W:                    | 2.6 kW                               |
|--------------------------------|--------------------------------------|
| Engine:                        | 4T, single cylinder, OHV, air cooled |
| Startup system\lgnition type:  | Rope start/TCI                       |
| Speed:                         | 2900 - 3000 rpm                      |
| Displacement:                  | 146 cc                               |
| Fuel:                          | Euro V                               |
| Fuel / oil tank                | 0.81/0.51                            |
| Fuel consumption:              | 0.45 l/h                             |
| Deck size:                     | 16"                                  |
| Bar size with cutting blade:   | 398 mm                               |
| Cutting height:                | 25 - 70 mm                           |
| Adjustable cutting height      | 6 Trepte                             |
| Individual height adjustment w | heBas;20 - 60 mm                     |
| Wheel size:                    | Fata 6"/ Spate 7"                    |
| Catcher / size:                | Da / 40 I                            |
| Trap function:                 | 3 in 1: - Collecting                 |
|                                | - Mulching                           |
|                                | - Rear discharge                     |

| Power kW/W:                     | 2.6 kW                               |
|---------------------------------|--------------------------------------|
| Engine:                         | 4T, single cylinder, OHV, air cooled |
| Startup system / Ignition type: | Rope start / TCI                     |
| Speed:                          | 2900 - 3000 rpm                      |
| Displacement:                   | 146 cc                               |
| Fuel:                           | Euro V                               |
| Fuel / oil tank                 | 0.81/0.51                            |
| Fuel consumption:               | 0.45 l/h                             |
| Deck size:                      | 17"                                  |
| Bar size with cutting blade:    | 420 mm                               |
| Cutting height:                 | 25 - 70 mm                           |
| Adjustable cutting height       | 5 speeds                             |
| Wheel size:                     | Front 6"/ Rear 7"                    |
| Washing nozzle:                 | Da                                   |
| Catcher / size:                 | Da / 40 I                            |
| Trap function:                  | 3 in 1: - Collecting                 |
|                                 | - Mulching                           |
|                                 | - Rear discharge                     |

| Power kW/W:                     | 2.6 kW                              |
|---------------------------------|-------------------------------------|
| Engine:                         | 4T, single cylinder OHV, air cooled |
| Startup system / Ignition type: | Rope start / TCI                    |
| Speed:                          | 2900 - 3000 rpm                     |
| Displacement:                   | 146 cc                              |
| Fuel:                           | Euro V                              |
| Fuel / oil tank                 | 0.8   / 0.5                         |
| Fuel consumption:               | 0.45 l/h                            |
| Deck size:                      | 18"                                 |
| Bar size with cutting blade:    | 457 mm                              |
| Cutting height:                 | 25 - 75 mm                          |
| Adjustable cutting height       | 7 Trepte                            |
| Wheel size:                     | Fata 7"/ Spate 10"                  |
| Washing nozzle:                 | Da                                  |
| Catcher / size:                 | Da / 60 I                           |
| Trap function:                  | 4 in 1: - Collecting                |
|                                 | - Mulching                          |
|                                 | - Rear discharge                    |
|                                 | - Lateral discharge                 |

| Power kW/W:                     | 2.6 kW                              |
|---------------------------------|-------------------------------------|
| Engine:                         | 4T, single cylinder OHV, air cooled |
| Startup system / Ignition type: | Rope start si electric / TCI        |
| Speed:                          | 2900 - 3000 rpm                     |
| Displacement:                   | 196 cc                              |
| Fuel:                           | Euro V                              |
| Fuel / oil tank                 | 0.81/061                            |
| Fuel consumption:               | 0.62 l/h                            |
| Deck size:                      | 21"                                 |
| Bar size with cutting blade:    | 525 mm                              |
| Cutting height:                 | 25 - 75 mm                          |
| Adjustable cutting height       | 7 Trepte                            |
| Wheel size:                     | Fata 8"/ Spate 11"                  |
| Washing nozzle:                 | Da                                  |
| Catcher / size:                 | Da / 70 I                           |
| Trap function:                  | 3 in 1: - Collecting                |
|                                 | - Mulching                          |
|                                 | - Rear discharge                    |
|                                 | - Lateral discharge                 |



### DZ-C308 EARTH AUGER (DRILL)

**1.5KW 52CC** Product type: Earth auger. New product!

| Power kW/HP:         | 1.5 kW/2.5 HP                   |
|----------------------|---------------------------------|
| Drilling diameter:   | Ø60 - Ø300                      |
| Drilling max. depth: | 800 mm                          |
| Drilling mechanism:  | Gear with rap. 30:1             |
| Lubrication:         | Lubrication by mechanism        |
| Rated speed:         | 8500 rpm                        |
| Maximum speed:       | 2700 - 3000 rpm                 |
| Auger max. speed:    | 200 rpm                         |
| Displacement:        | 51.7 CC                         |
| Engine:              | 2T, single cylinder, air cooled |
| Carburetor type:     | Carburator cu membrana          |
| Compression ratio:   | 25:1 (gasoline:oil)             |
| Fuel:                | Unleaded gasoline               |
| Auger size:          | 200 x 800 mm                    |



### DZ-C233 PILE DRIVER 2.5NM 1350BPM ENGINE 52CC

2 STROKE Product type: Pile driver. New product!

| Power kW/HP:                 | 1.5 kW/2.0 CP      |
|------------------------------|--------------------|
| Engine:                      | 2T, monocilinder   |
| Impact energy:               | 20-55 J            |
| Impact rate:                 | 700-1350 bpm       |
| Max. torque:                 | 2.5 Nm             |
| Engine speed at max. torque: | 5000 rpm           |
| Fuel consumption:            | <u>≺</u> 0.6 l/h   |
| Compression ratio:           | 25:1               |
| Starting:                    | Manual             |
| Noise level:                 | 115 dB             |
| Maximum engine speed:        | 7000 rpm           |
| Fuel:                        | Benzina fara plumb |
| Displacement:                | 52 CC              |
| Fuel tank capacity:          | 1.3                |



### DZ-C234

PILE DRIVER 1.8NM, 2000BPM, ENGINE 44CC 2 STROKE

Product type: driver. New product!

| Power kW/HP:                 | 1 kW/1.34 HP        |
|------------------------------|---------------------|
| Engine:                      | 2T, single cylinder |
| Impact energy:               | 45 J                |
| Impact rate:                 | 1500-2000 bpm       |
| Max. torque:                 | 1.8 Nm              |
| Engine speed at max. torque: | 5000 rpm            |
| Fuel consumption:            | ≤ 0.45 l/h          |
| Compression ratio:           | 25:1                |
| Starting:                    | Manual              |
| Noise level:                 | 108.5 dB            |
| Maximum engine speed:        | 9000 rpm            |
| Fuel:                        | Unleaded petrol     |
| Displacement:                | 44 CC               |
| Fuel tank capacity:          | 0.75                |

2022



### **DZ-SE126**

### SCRISSORS WITH BATTERY 3.6V FOR LAWN / HEDGE

| Operating period:  | cca. 40min           |
|--------------------|----------------------|
| Charging duration: | 3.5 ore              |
| Cutting width:     | 80 mm                |
| Blade length:      | 120 mm (steel blade) |
| Knife length:      | 1100 rpm             |
| Battery capacity:  | 1.3 Ah               |
| Voltage:           | 3.6 V                |





### **DZ-SE147**

CHAINSAW WITH BATTERY 18V 2AH


| Battery:            | Lithium-Ion |
|---------------------|-------------|
| Voltage:            | 18 V        |
| Cutting capacity:   | 110 mm      |
| Frequency :         | 50-60 Hz    |
| Battery capacity:   | 2000 mAh    |
| Engine speed (rpm): | 3000 rpm    |



**DZ-C208** HAMMER WITH MAGNET



**DZ-C209** CONCRETE FORGING PLIERS 300MM





**DZ-SE148** GARDEN ELECTRIC SCISSORS WITH BATTERY

| Battery:            | Lithium-Ion |
|---------------------|-------------|
| Size:               | 34x10x29    |
| Operating period:   | 2-4 h       |
| Power KW/W:         | 100 W       |
| Voltage:            | 210-240 V   |
| Cutting capacity:   | 1-30 mm     |
| Max. blade opening: | 40 mm       |
| Voltage VCD:        | 42          |
| Vibration level:    | 2.5 m/s     |
| Net weight:         | 1.1 kg      |
| Battery capacity:   | 2 Ah        |
| Max. consumption:   | 42.6 Wh     |



DZ-C249 AXE WITH FIBERGLASS HANDLE 600G

| Weight:            | 0.6 kg                  |
|--------------------|-------------------------|
| Blade width:       | 3 cm                    |
| Material - blade:  | steel OL45              |
| Material - handle: | fiberglass with plastic |
|                    | finishing               |
| Product type       | Axe                     |



DZ-C250 AXE WITH FIBERGLASS HANDLE 1250G

| Weight:            | 1.25 kg           |
|--------------------|-------------------|
| Blade width:       | 3 cm              |
| Material - blade:  | steel OL45        |
| Material - handle: | fiberglass with   |
|                    | plastic finishing |
| Handle length:     | 82 cm             |



DZ-C248 SPLIT AXE WITH FIBERBLASS HANDLE 2000G

| Weight:            | 2 kg                    |
|--------------------|-------------------------|
| Blade width:       | 3 cm                    |
| Material - blade:  | steel OL45              |
| Material - handle: | fiberglass with plastic |
|                    | finishing               |
| Handle length:     | 82 cm                   |



DZ-C251 AXE WITH FIBERGLASS HANDLE 2000G

| Weight:            | 2 kg              |
|--------------------|-------------------|
| Blade width:       | 3 cm              |
| Material - blade:  | steel OL45        |
| Material - handle: | fiberglass with   |
|                    | plastic finishing |
| Handle length:     | 82 cm             |



### **DZ-SE256** HYDRAULIC CAR JACK BOTTLE 2T

Field of use: Auto

| Lifting capacity: | 2 Tones   |
|-------------------|-----------|
| Minimum height:   | 181 mm    |
| Maximum height:   | 354 mm    |
| Safety valve:     | Yes       |
| Drive type:       | Hydraulic |



### **DZ-SE257** HYDRAULIC CAR **JACK BOTTLE 4T**

Field of use: Auto

| Lifting capacity: | 4 Tones   |
|-------------------|-----------|
| Minimum height:   | 194 mm    |
| Maximum height:   | 372 mm    |
| Safety valve:     | Yes       |
| Drive type:       | Hydraulic |



### **DZ-SE258** HYDRAULIC CAR **JACK BOTTLE 6T**

Field of use: Auto

| Lifting capacity: | 6 Tones   |
|-------------------|-----------|
| Minimum height:   | 216 mm    |
| Maximum height:   | 413 mm    |
| Safety valve:     | Yes       |
| Drive type:       | Hydraulic |

**DZ-SE259** HYDRAULIC FLOOR JACK 2T CROCODILE

Field of use: Auto

| Lifting capacity: | 6 Tones   |
|-------------------|-----------|
| Minimum height:   | 216 mm    |
| Maximum height:   | 413 mm    |
| Safety valve:     | Yes       |
| Drive type:       | Hydraulic |



### DZ-CI107 HIGH PRESSURE WASHER 105BAR 1400W

Product type: High pressure washer. New product!

| Engine:                           | Electric without brushes |
|-----------------------------------|--------------------------|
| Power kW/W:                       | 1400 W                   |
| Working pressure:                 | 70 bari                  |
| Maximum pressure:                 | 105 bar                  |
| Working flow:                     | 5.5 l/min                |
| Maximum flow:                     | 6.8 l/min                |
| Noise level:                      | 70 dB                    |
| Insulation class:                 | Ш                        |
| Lance and hose coupling:          | M14 x 1.5                |
| Max. pressure hose and lance:     | 220 bar                  |
| Pressure hose length:             | 5 m                      |
| Water temperature:                | 5°C-50°C                 |
| Tightness class:                  | IPX5                     |
| Electric cable length:            | 5 m                      |
| Jet type and adjustable pressure: | At the nozzle            |

| Engine:                           | Electric without brushes |
|-----------------------------------|--------------------------|
|                                   | 1600 W                   |
| Working pressure:                 | 90 bar                   |
| Maximum pressure:                 | 135 bar                  |
| Working flow:                     | 5.5 l/min                |
| Maximum flow:                     | 8 l/min                  |
| Noise level:                      | 97 dB                    |
| Insulation class:                 |                          |
| Lance and hose coupling:          | M14 x 1.5                |
| Max. pressure hose and lance:     | 220 bar                  |
| Pressure hose length:             | 5 m                      |
| Water temperature:                | 5°C-50°C                 |
| Tightness class:                  | IPX5                     |
| Electric cable length:            |                          |
| Jet type and adjustable pressure: | At the nozzle            |

| Engine                            | Electric without brushes |
|-----------------------------------|--------------------------|
| Engine:                           | Electric without brushes |
| Power kW/W:                       | 1800 W                   |
| Working pressure:                 | 105 bar                  |
| Maximum pressure:                 | 135 bar                  |
| Working flow:                     | 6 I/min                  |
| Maximum flow:                     | 7.5 l/min                |
| Noise level:                      | 98 dB                    |
| Insulation class:                 | II.                      |
| Lance and hose coupling:          | M14 x 1.5                |
| Max. pressure hose and lance:     | 220 bar                  |
| Pressure hose length:             | 5 m                      |
| Water temperature:                | 5°C-50°C                 |
| Tightness class:                  | IPX5                     |
| Electric cable length:            | 5 m                      |
| Jet type and adjustable pressure: | At the nozzle            |

| Engine:                           | Electric without brushes |
|-----------------------------------|--------------------------|
| Power kW/W:                       | 2400 W                   |
| Working pressure:                 | 120 bar                  |
| Maximum pressure:                 | 180 bar                  |
| Working flow:                     | 5.5 l/min                |
|                                   | 8 I/min                  |
| Noise level:                      | 94 dB                    |
|                                   | Ш                        |
| Lance and hose coupling:          | M14 x 1.5                |
| Max. pressure hose and lance:     | 220 bar                  |
| Pressure hose length:             | 5 m                      |
|                                   | 5°C-50°C                 |
| Tightness class:                  | IPX5                     |
| Electric cable length:            | 5 m                      |
| Jet type and adjustable pressure: | At the nozzle            |



### **DZ-CI108**

HIGH PRESSURE WASHER 135BAR 1600W

Product type: High pressure washer. New product!

## 

### DZ-CI109

HIGH PRESSURE WASHER 155BAR 1800W

Product type: High pressure washer. New product!

| DEIDOLE |
|---------|
|         |

### DZ-CI110

HIGH PRESSURE WASHER 180BAR 2400W

Product type: High pressure washer. New product!

24



### **DZ-CI111**

LANCE FOR HIGH PRESSURE WASHER

| Product type: Lance           | Lance                |
|-------------------------------|----------------------|
| Compatible with high pressure |                      |
| washer:                       | DZ-CI107 si DZ-CI108 |



### DZ-CI114

LANCE TURBO HIGH PRESSURE WASHER

| Product type: Lance           | Lance              |
|-------------------------------|--------------------|
| Compatible with high pressure |                    |
| washer:                       | DZ-CI109, DZ-CI110 |



### DZ-CI117

LANCE 3 JETS FOR HIGH PRESSURE WASHER

| Flounce type. | Lance |  |
|---------------|-------|--|
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |
|               |       |  |



### DZ-CI118 LANCE SPRAY FOR HIGH PRESSURE WASHER

| Product type: | Extension lance |
|---------------|-----------------|
|               |                 |
|               |                 |
|               |                 |
|               |                 |
|               |                 |
|               |                 |
|               |                 |
|               |                 |

Product type:

Water gun





### DZ-CI119

WATER GUN FOR HIGH PRESSURE WASHER



### DZ-CI120

PRESSURE HONE FOR HIGH PRESSURE WASHER





### DZ-SE156

UNIVERSAL BATTERY 20V/2AH DZ-SE129,132,133,134,135,137

| Battery capacity: | 2 Ah |
|-------------------|------|
| Battery:          |      |
|                   |      |



### DZ-CI112

ROTARY BRUSH FOR HIGH PRESSURE WASHER

| Product type:                 | Rotary bru |
|-------------------------------|------------|
| Compatible with high pressure |            |
|                               | DZ-CI107 9 |

### **DZ-CI113**

ROTARY BRUSH WITH HANDLE FOR HIGH PRESSURE WASHER

| Product type:                 | Rotary brush         |
|-------------------------------|----------------------|
| Diameter:                     | 30 cm                |
| Height:                       | 15 cm                |
| Compatible with high pressure |                      |
| washers:                      | DZ-CI107 si DZ-CI109 |

|           | _ |     |   |
|-----------|---|-----|---|
| <b>D7</b> |   | 111 |   |
| UL        | - |     |   |
|           |   |     | - |

ROTARY BRUSH FOR HIGH PRESSURE WASHER

| Product type:                 | Rotary brush       |
|-------------------------------|--------------------|
| Compatible with high pressure |                    |
| washers:                      | DZ-CI109, DZ-CI110 |



### **DZ-CI116**

ROTARY WASHING BRUSH CU MANER FOR HIGH PRESSURE WASHER 
 Product type:
 Rotary brush

 Compatible with high pressure
 washers:

 DZ-CI109, DZ-CI110

### **DZ-CI121**

BRUSH FOR HIGH PRESSURE WASHERS DZ-CI107, DZ-CI108

| Product type:                 | Fixed brush        |
|-------------------------------|--------------------|
| Compatible with high pressure |                    |
| washers:                      | DZ-CI107, DZ-CI108 |
| Material:                     | Plastic            |
| Height:                       |                    |
| Length:                       | 420 mm             |

Home and camping



### **DZ-CI122**

BRUSH FOR HIGH PRESSURE WASHERS DZ-CI109, DZ-CI110

| Product type:                 | Fixed brush        |
|-------------------------------|--------------------|
| Compatible with high pressure |                    |
| washers:                      | DZ-CI109, DZ-CI110 |
| Material:                     | Plastic            |
| Height:                       |                    |
| Length:                       | 420 mm             |





### DZ-CI102

VACUUM CLEANER WITH BATTERY 120W, 0,8L 2200MAH

Product type: Vacuum cleaner with battery. New product!

| Power kW/HP:            | 0.12 kW/0.16CP  |
|-------------------------|-----------------|
| Capacity:               | 0.81            |
| Min./max. working time: | 24/50 min       |
|                         | 10 kPa          |
| Voltage:                | 21.6V, 2200 Mah |
| Dust bin:               | Without bag     |



### DZ-CI103 WET/DRY VACUUM CLEANER 1000 W 15 L

Product type: Wet/dry vacuum cleaner. New product!

| Power kW/HP:   | 1 kW/1.34 CP             |
|----------------|--------------------------|
| Capacity: 15 I | 15 I                     |
| Suction power: | 160 mbar/16 kPa          |
| Body material: | Inox                     |
| Noise level:   | 84 dB                    |
| Use:           | Wet/dry surface cleaning |
| Dust bin:      | With bag                 |



### DZ-CI104 WET/DRY VACUUM CLEANER 1000 W 20 L

Product type: Wet/dry vacuum cleaner. New product!

| Power kW/HP:   | 1 kW/1.34 CP     |
|----------------|------------------|
| Capacity: 15 I |                  |
| Suction power: | 160 mbar/16 kPa  |
| Body material: |                  |
| Noise level:   | 84 dB            |
| Use:           | Wet/dry surfaces |
| Dust bin:      | With bag         |



### DZ-CI105 WET/DRY VACUUM CLEANER 1250 W 25 L

Product type: Wet/dry vacuum cleaner. New product!

| Power kW/HP:   | 1.25 kW/1.68 CP          |
|----------------|--------------------------|
| Capacity: 15 I | 251                      |
| Suction power: | 160 mbar/16 kPa          |
| Body material: | Inox                     |
| Noise level:   | 84 dB                    |
| Use:           | Wet/dry surface cleaning |
| Dust bin:      | With bag                 |

2022



### DZ-CI106

ASH VACUUM CLEANER 1200W 18 L

Product type: Ash vacuum cleaner. New product!

| Power kW/HP:   | 1.2 kW/1.63 CP  |
|----------------|-----------------|
| Capacity: 15 I | 18              |
| Suction power: | 180 mbar/18 kPa |
| Body material: |                 |
| Noise level:   | 84 dB           |
| Use:           |                 |
| Dust bin:      | Without bag     |



TELESCOPIC LADDER 2M - 7 STEPS Product type: Telescopic ladder. New product!

| Ladder type:        | Telescopic |
|---------------------|------------|
| Minimum height:     | 0.6 m      |
| Maximum height:     | 2 m        |
| Number of sections: |            |
| Number of steps:    | 7          |
| Maximum weight:     | 150 Kg     |
| Material:           | Aluminium  |
| Colour:             |            |

|   |    | - 7 |
|---|----|-----|
|   |    |     |
| _ |    |     |
|   |    | -   |
|   | 55 | 4   |
| - | 3  |     |
|   | -  | -   |
|   |    |     |

DZ-C243 TELESCOPIC LADDER 2.9M - 10 STEPS

Product type: Telescopic ladder. New product!

| Ladder type:        | Telescopic |
|---------------------|------------|
| Minimum height:     | 0.69 m     |
| Maximum height:     | 2.9 m      |
| Number of sections: |            |
| Number of steps:    | 10         |
| Maximum weight:     | 150 Kg     |
| Material:           | Aluminium  |
| Colour:             |            |

|  | F |
|--|---|
|  |   |
|  |   |

### DZ-C244

TELESCOPIC LADDER 3.8M - 13 STEPS

Product type: Telescopic ladder. New product!

| Ladder type:     | Telescopic |
|------------------|------------|
| Minimum height:  | 0.8 m      |
| Maximum height:  | 3.8 m      |
|                  |            |
| Number of steps: | 13         |
|                  | 150 Kg     |
| Material:        | Aluminium  |
| Colour:          |            |

|   | σ      |
|---|--------|
|   | Ċ      |
|   |        |
|   | 0      |
|   |        |
|   |        |
|   | σ      |
|   | O      |
| - | 5      |
|   |        |
|   | С<br>П |
|   | σ      |
|   | (1)    |
|   | č      |
|   |        |
|   | 0      |
|   |        |



### DZ-C245

TELESCOPIC LADDER 4.4M - 15 STEPS

Product type: Telescopic ladder. New product!

| Ladder type:        | Telescopic |
|---------------------|------------|
| Minimum height:     | 0.94 m     |
| Maximum height:     | 4.4 m      |
| Number of sections: | 1          |
| Number of steps:    | 15         |
| Maximum weight:     | 150 Kg     |
| Material:           | Aluminium  |
| Colour:             | Silver     |



### **DZ-C246**

### DOUBLE TELESCOPIC LADDER 3.2M - 10 STEPS

Product type: Double telescopic ladder. New product!

| Ladder type:        | Telescopic |
|---------------------|------------|
| Minimum height:     | 0.85 m     |
| Maximum height:     | 3.2 m      |
| Number of sections: |            |
| Number of steps:    | 10         |
| Maximum weight:     | 150 Kg     |
| Material:           | Aluminium  |
| Colour:             | Silver     |



| AA | i |
|----|---|
|    |   |

### DZ-C247 TELESCOPIC LADDER DUBLA 4.4M - 14 STEPS

Product type: Double telescopic ladder. New product!

| Ladder type:        | Telescopic |
|---------------------|------------|
| Minimum height:     | 0.91 m     |
| Maximum height:     | 4.4 m      |
| Number of sections: | 2          |
| Number of steps:    | 14         |
| Maximum weight:     | 150 Kg     |
| Material:           | Aluminium  |
| Colour:             |            |



### DZ-EI106

INDUSTRIAL DIESEL HEATER 220-240V 50HZ 20KW Product type: Industrial diesel

heater. New product!

| Heated area:                   | 150 mp                 |
|--------------------------------|------------------------|
| Engine:                        | YD-8040 (IP44)         |
| Power kW/W:                    | 20 kW                  |
| Engine power:                  |                        |
| Fuel:                          | Diesel                 |
| Tank capacity:                 |                        |
| Consumption:                   | 1.7 l/h                |
| Noise level:                   | 75 dB                  |
| Body material:                 | Metal (0.8 mm)         |
| Work temperature:              | 35°C-60°C              |
| Thermostat:                    | Yes                    |
| Electric engine intensity:     | 0.8 A                  |
| Heating type:                  | Direct                 |
| Speed:                         | 1 speed                |
| Air flow:                      | 600 m³/h               |
| Heating:                       | 68240 BTU              |
| Temperature status calculator: | Yes (PIN: 2531CT-0216) |
| Flame sensor:                  | Yes                    |
| Stainless steel combustion     |                        |
| chamber with fan cooling:      | Yes                    |
| Safety protection:             |                        |
| Cut-off temperature in case of |                        |
| overheating:                   | Yes                    |
| Fuel refueling indicator:      | Yes                    |



### DZ-EI107

INDUSTRIAL DIESEL HEATER 220-240V 50HZ 50KW

Product type: Industrial diesel heater. New product!

| Engine:                        | YD-9045 (IP44)         |
|--------------------------------|------------------------|
| Power kW/W:                    | 50 kW                  |
|                                | 350W                   |
| Fuel:                          | Diesel                 |
|                                |                        |
| Consumption:                   | 4 l/h                  |
|                                |                        |
| Body material:                 | Metal (0.8 mm)         |
| Work temperature:              | 35°C-60°C              |
| Thermostat:                    | Yes                    |
| Electric engine intensity:     | 1.52 A                 |
| Heating type:                  | Direct                 |
|                                |                        |
| Air flow:                      | 1100 m³/h              |
| Temperature status calculator: | Yes (PIN: 2531CT-0216) |
| Flame sensor:                  | Yes                    |
|                                |                        |
| chamber with fan cooling:      | Yes                    |
| Safety protection:             | Yes                    |
| Cut-off temperature in case of |                        |
|                                |                        |
| Fuel refueling indicator:      | Yes                    |
| Wheels size:                   | 200 mm                 |

400 mp

Heated area:





### **DZ-EI108**

LPG GAS FORCED HEATER 220-240V 50HZ 15KW

Product type: Gas forced heater. New product!

| ( | N            |
|---|--------------|
| ( | N            |
|   | $\mathbf{D}$ |
| ( | N            |



### DZ-EI109 LPG GAS FORCED HEATER 220-240V 50HZ 30KW

Product type: Gas forced heater. New product!

| Heated area: 100 mp                  | 100 mp            |
|--------------------------------------|-------------------|
| Engine: YXG-30/50M (IP44)            | YXG-30/50M (IP44) |
| Power kW/W: 30 kW                    | 30 kW             |
| Fuel consumption: 2.18 l/h           | 2.18 l/h          |
| Fuel: LPG propane gas                | LPG propane gas   |
| Noise level: 48 dB                   | 48 dB             |
| Body material: Metal (0.6 mm)        | Metal (0.6 mm)    |
| Work temperature: 35°C-60°C          | 35°C-60°C         |
| Cut-off temperature in case of       | 85°C              |
| overheating:                         | 870 m³/h          |
| 85°C                                 | 102360 BTU        |
| Air flow: 870 m³/h                   |                   |
| Heating: 102360 BTU                  | Yes               |
| Mains power supply: Yes              | 18 hours          |
| Gas cylinder supply: Yes             | 0.7 bar           |
| Duration of continuous use: 18 hours | 1.5 m             |
| Gas pressure: 0.7 bar                | Yes               |
| Coupling size: 1.5 m                 |                   |
| Power regulator: Yes                 |                   |
| Special nozzle with strong oxygen    | Yes               |
| supply: Yes                          |                   |
| Safety protection for leakages: Yes  | Yes               |
| Flame monitoring in the combustion   | Yes               |
| chamber: Yes                         | IP24              |

| Heated area:                           | 20 mp            |
|--|------------------|
| Engine:                                | YZF48213H(IP44)  |
| Power kW/W:                            | 2000 W           |
| Number of sections:                    |                  |
| Heating power:                         | Step I: 20 W     |
|  | Step II: 1000 W  |
|  | Step III: 2000 W |
| Noise level:                           | 51 dB            |
| Insulation class:                      | В                |
| Material:                              | Metal (0.6 mm)   |
| Thermostat:                            | Yes              |
| Air flow:                              | 272 m³/h         |
| Safety protection:                     | Yes              |
| Overheating protection:                | Yes              |
| Waterproof class:                      | IP24             |
| Heating elements:                      | Inox             |
| Max. produced temperature:             | 40°C             |
| Restart temperature after overheating: |                  |

30 mp

3000 W



### DZ-EI110

INDUSTRIAL FAN HEATER 25/1000/2000W

Product type: Air heater. New product!

|   | Engine:                                | YZF482     |
|---|--|------------|
|   | Power kW/W:                            | 3000 W     |
|   | Number of sections:                    |            |
|   | Heating power:                         | Step I: 2  |
|   |  | Step II: 2 |
|   |  | Step III:  |
|   | Noise level:                           | 53 dB      |
| 2 | Insulation class:                      | В          |
|   | Material:                              | Metal (0   |
|   | Thermostat:                            | Yes        |
|   | Air flow:                              | 272 m³/l   |
|   | Safety protection:                     | Yes        |
|   | Overheating protection:                |            |
|   | Waterproof class:                      | IP24       |
|   | Heating elements:                      |            |
|   | Max. produced temperature:             | 40°C       |
|   | Restart temperature after overheating: | Yes        |
|   |  |            |

Heated area:

Home and camping



### **DZ-EI111**

INDUSTRIAL FAN HEATER 30/1500/3000W

Product type: Air heater. New product!



### DZ-EI112 INDUSTRIAL PTC FAN HEATER, 20/1000/2000W

Product type: Air heater. New product!

| Heated area:                           | 20 mp                     |
|--|---------------------------|
|  | YJ58-16                   |
| Power kW/W:                            | 2000 W                    |
|  | 3                         |
| Heating power on steps:                | I: 20/II: 1000/III:2000 W |
|  | 43 dB                     |
| Insulation class:                      | E                         |
|  | Metal (0.6 mm)            |
| Air flow:                              | 127 m³/h                  |
| Safety protection:                     | Yes                       |
| Restart temperature after overheating: | Yes                       |
|  | Yes                       |
| Overheating protection:                | Yes                       |
| Max. produced temperature:             | 40°C                      |
| Restart temperature after overheating: | PTC                       |
|  | IP20                      |

| Heated area:                           | 30 mp                      |
|--|----------------------------|
|  | YJ58-20                    |
| Power kW/W:                            | 3000 W                     |
|  | 3                          |
| Heating power on steps:                | I: 25/II: 1500/III: 3000 W |
|  | 48 dB                      |
| Insulation class:                      | E                          |
|  | Metal (0.6 mm)             |
| Air flow:                              | Yes                        |
| Safety protection:                     | 340 m³/h                   |
| Restart temperature after overheating: | Yes                        |
| Mains power supply:                    | Yes                        |
| Overheating protection:                | Yes                        |
| Max. produced temperature:             | 40°C                       |
| Restart temperature after overheating: | РТС                        |
| Waterproof class:                      | IP20                       |



### DZ-EI1113 INDUSTRIAL PTC FAN HEATER, 25/1500/3000W

Product type: Air heater. New product!

| 10 | • |
|----|---|

### DZ-CB100

ELECTRIC MEAT GRINDER 1400W

Product type: Electric meat grinder. New product!

| Power kW/HP:      | 1.4 kW/1.9 CP |
|-------------------|---------------|
|                   | 1.6 Kg/min    |
| Material:         | Metal         |
|                   |               |
| Switch sensor:    | Yes           |
| Voltage:          |               |
| Frequency:        | 50 Hz         |
| Work temperature: | 5°C - 40°C    |



### **DZ-CB101**

STAINLESS STEEL ELECTRIC MEAT GRINDER 1400W MGG-140

Product type: Electric meat grinder. New product!

| Power kW/HP:      | 1.4 kW/1.9 CP |
|-------------------|---------------|
|                   | 1.6 Kg/min    |
| Material:         | Metal         |
|                   |               |
| Switch sensor:    | Yes           |
| Voltage:          | 230 V         |
| Frequency:        | 50 Hz         |
| Work temperature: | 5°C - 40°C    |



### DZ-CB102 SINGLE INDUCTION COOKER 1500W

Product type: Induction cooker. New product!

| Power kW/W:                | 1500 W                 |
|----------------------------|------------------------|
|                            |                        |
| Case material:             | Plastic                |
| Cooking surface material:  | Ceramic                |
| Coiling:                   | Copper coated aluminum |
| Cooking functions :        |                        |
| Power setting levels:      |                        |
| Temperature level setting: | 8                      |
| Cooking timer:             | 4 hours                |
| Preset functions:          | 24 hours               |
| Overheating safety:        | Yes                    |
| Overvoltage safety:        | Yes                    |
|                            |                        |
| Auto shut down function:   | Yes                    |
|                            | 28 x 34 x 62 cm        |
| Plate size:                | 25 x 25 cm             |



### DZ-EI114 ELECTRIC HEATER 1000W/2000W, ALB

Product type: Electric heater. New product!

| Heated area:               | 20 mp                 |
|----------------------------|-----------------------|
| Power kW/W:                | 2000 W                |
| Speed:                     | 2                     |
| Heating power on steps:    | I: 1000 / II: 2000 W  |
| Thermostat:                | Yes                   |
| Front material:            | Tempered glass (4 mm) |
| Body material:             | Metal (0.8 mm)        |
| Heating elements:          | X-shaped aluminum     |
| Max. produced temperature: | 49°C                  |
|                            |                       |
|                            |                       |
| Wi-Fi function:            | Yes                   |



### DZ-EI115

ELECTRIC HEATER 1000W/2000W, NEGRU

Product type: Electric heater. New product!

| Heated area:               | 20 mp                 |
|----------------------------|-----------------------|
| Power kW/W:                | 2000 W                |
| Speed:                     | 2                     |
| Heating power on steps:    | I: 1000 / II: 2000 W  |
| Thermostat:                | Yes                   |
| Front material:            | Tempered glass (4 mm) |
| Body material:             | Metal (0.8 mm)        |
| Heating elements:          | X-shaped aluminum     |
| Max. produced temperature: | 49°C                  |
| Restart temperature after  |                       |
| overheating:               |                       |
| Wi-Fi function:            | Yes                   |



### DZ-CI100

MANUAL SWEEPER 700MM 14L MS70

Product type: Manual sweeper. New product!

| Operating method:      | Manual    |
|------------------------|-----------|
| Dirt tank capacity:    | 14 I      |
| Max. speed:            | 4 km/h    |
| Max. sweeping surface: | 2800 m²/h |
| Action width:          | 700 mm    |



### DZ-CI101 MANUAL SWEEPER 800MM 30L MS80-A

Product type: Manual sweeper. New product!

| Operating method:      | Manual    |
|------------------------|-----------|
| Dirt tank capacity:    | 301       |
| Max. speed:            | 4 km/h    |
| Max. sweeping surface: | 3200 m²/h |
| Action width:          | 800 mm    |



### **DZ-EI105**

SPRAY GAS RESERVE 227G 410ML

| Product t | vne: Gas | reserve |
|-----------|----------|---------|
| TTOQUEL   | ype. Ous | 10301VC |

| Product type: | Gas reserve |
|---------------|-------------|
| Quantity:     | 410 ml      |

Gas re



### DZ-EI116 GAS RESERVE 190G FOR PLUMBER LAMP

| 1 |  |
|---|--|
|   |  |
|   |  |

Product type: Gas reserve



### DZ-CB103 RECHARGEABLE

COMPOSITE CYLINDER 2KG/5L

Product type: Rechargeable cylinder

| Capacity:                             | 51                                |
|---------------------------------------|-----------------------------------|
| Fuel:                                 | LPG propane gas; butane gas       |
| Cylinder max. pressure:               | 30 bar                            |
| Max. pressure at the discharge valve: | 25 bar                            |
| Valve hydrostatic max. pressure:      | 45 bar                            |
| Material:                             | Fibra de sticla + invelis plastic |
| Size:                                 | 40 x 32 cm                        |

2022



### **DZ-CB104**

RECHARGEABLE COMPOSISTE CYLINDER 6KG/14L

Product type: Rechargeable cylinder

| Capacity:                             | 14 I                        |
|---------------------------------------|-----------------------------|
| Fuel:                                 | LPG propane gas; butane gas |
| Cylinder max. pressure:               | 30 bar                      |
| Max. pressure at the discharge valve: | 25 bar                      |
| Valve hydrostatic max. pressure:      | 45 bar                      |
| Material:                             |                             |
| Size:                                 | 49 x 32 cm                  |



### DZ-CB105 RECHARGEABLE

COMPOSISTE CYLINDER 10KG/24L

Product type: Rechargeable cylinder

| Capacity:                             | 241                               |
|---------------------------------------|-----------------------------------|
| Fuel:                                 | LPG propane gas; butane gas       |
| Cylinder max. pressure:               | 30 bar                            |
| Max. pressure at the discharge valve: | 25 bar                            |
| Valve hydrostatic max. pressure:      | 45 bar                            |
| Material:                             | Fibra de sticla + invelis plastic |
| Size:                                 | 59 x 32 cm                        |





EXTENSIBLE DRYWALL SANDER WITH VACUUM CLEANER Ø215 750W

Classification: DRYWALL SANDERS WITH VACUUM CLEANER

Adjustable handle
Dust bag

### DZ-C201

EXTENSIBLE DRYWALL SANDER Ø215 750W

Classification: ELECTRIC DRYWALL SANDERS WITH VACUUM CLEANER

Adjustable handleFoldable and extandable

### Power: 750W Speed: 1000-1600 rpm Sanding disc diameter: Ø215 mm Suction hose length: 2m Working area LED light: 15W

| Power:                  | 750W          |
|-------------------------|---------------|
| Speed:                  | 1000-1600 rpm |
| Sanding disc diameter:  | Ø215 mm       |
| Suction hose length:    | 4m            |
| Working area LED light: | 15W           |

### DZ-C206

FOLDABLE DRYWALL SANDER WITH LED 750W Ø225MM

Classification: ELECTRIC DRYWALL SANDERS WITH VACUUM CLEANER

• LED for lighting the working area

Vacuum bagFoldable and extandable

| Power:                      | 750W         |
|-----------------------------|--------------|
| Speed:                      | 800-1700 rpm |
| Sanding disc:               | ø215 mm      |
| Abrasive disc:              | ø225 mm      |
| Telescopic foldable handle: | 1200-1800mm  |

# DIY Products



### **DZ-C218**

### EXTENSIBLE DRYWALL SANDER WITH VACUUM CLEANER AND BAG

Classification: ELECTRIC DRYWALL SANDERS WITH VACUUM CLEANER

• Extensible handle

| Power:                  | 710W                     |
|-------------------------|--------------------------|
| Speed:                  | 1000-1700 rpm            |
| Sanding disc diameter:  | Ø215 mm                  |
| Abrasive paper size:    | Ø225mm (granulație       |
|                         | #80/100/120/150/180/240) |
| Working area LED light: | 10W                      |
| Suction hose with bag:  | 2m                       |

2022



### DZ-C210

DRYWALL SANDER 750W 180MM

Classification: ELECTRIC DRYWALL SANDERS WITH VACUUM CLEANER

Dust discharge nozzleContinuous operation lock button

| 750W          |
|---------------|
| 1300-2500 rpm |
| Ø180 mm       |
| 2m            |
| 8W            |
|               |



WOOD ELECTRIC SANDER WITH BAND 360M/MIN 900W

| Power:         | 900 W        |
|----------------|--------------|
| Maximum speed: | 1900 rot/min |
| Speed:         | 360 m/min    |
| Band size:     | 76 X 533 mm  |

Classification: ELECTRIC SANDERS WITH BAND



### DZ-SE179 TRIANGLE DETAIL SANDER 180W 1400RPM

Classification: ELECTRIC SANDERS WITH VACUUM

Collecting box

| Power:          | 108 W         |
|-----------------|---------------|
| Maximum speed:  | 14000 rot/min |
| Collecting box: | Yes           |



### DZ-C268

SAND PAPER P80 6HOLES 215MM (1BUC=10PCS)

Classification: CONSUMABLES FOR ELECTRIC SANDERS

| Diameter: | 215 mm |
|-----------|--------|
| Set:      | 10 pcs |

215 mm

Diameter:

Set



### DZ-C269 SAND PAPER P120 6HOLES 215MM(1BUC=10PCS)


Classification: CONSUMABLES FOR ELECTRIC SANDERS




### DZ-C270

SAND PAPER P150 6HOLES 215MM (1BUC=10PCS)

Classification: CONSUMABLES FOR ELECTRIC SANDERS






### DZ-C271

SAND PAPER P80 10HOLES 207MM (1BUC=10PCS)

Classification: CONSUMABLES FOR ELECTRIC SANDERS

| Diameter: | 207 mm |
|-----------|--------|
| Set:      | 10 pcs |



SANDERS

SAND PAPER P120 10HOLES 207MM (1BUC=10PCS)

Classification: CONSUMABLES FOR ELECTRIC

| Diameter: | 207 mm |
|-----------|--------|
| Set:      | 10 pcs |

### **DZ-C273**

SAND PAPER P150 10HOLES 207MM (1BUC=10PCS)

Classification: CONSUMABLES FOR ELECTRIC SANDERS

| Diameter: | 207 mm |
|-----------|--------|
| Set:      | 10 pcs |



### **DZ-C274**

SAND PAPER P80 8HOLES 180MM (1BUC=10PCS)

Classification: CONSUMABLES FOR ELECTRIC SANDERS


| Diameter: | 180 mm |
|-----------|--------|
| Set:      | 10 pcs |



**DZ-C275** 

SAND PAPER P1208HOLES 180MM (1BUC=10PCS)

Classification: CONSUMABLES FOR ELECTRIC SANDERS






### **DZ-C276**

SAND PAPER P150 8HOLES 180MM (1BUC=10PCS)

Classification: CONSUMABLES FOR ELECTRIC SANDERS



### **DZ-C222**


ELECTRIC SANDER FOR WET CONCRETE

Classification: WET CONCRETE SANDER

Included accessories:

1 plastic grinding disc

1 sponge grinding disc
1 abrasive paper disc
2 straight / cross screwdrivers











PAINT/MORTAR MIXER 1200W 50CM

Classification: MORTAR OR PAINT ELECTRICAL MIXERS

| Power:             | 1200 W      |
|--------------------|-------------|
| Paddle size:       | ø120 mm     |
| Connecting system: | M14         |
| 2 speeds:          |             |
| - Speed I:         | 240-500 rpm |
| - Speed II:        | 380-850 rpm |

**DZ-C205** PAINT/MORTAR MIXER 1300W, **MIXER, 2 SPEEDS** 

Classification: MORTAR OR PAINT ELECTRICAL MIXERS

| Power:             | 1300 W      |
|--------------------|-------------|
| LED working light: | Da          |
| Paddle size:       | ø120 mm     |
| 2 speeds:          |             |
| - Speed I:         | 180-430 rpm |
| - Speed II         | 300-680 rpm |
| Connecting system: | M14         |

**DZ-C220** PAINT/MORTAR MIXER

2 SPEEDS 1800W

Classification: MORTAR OR PAINT ELECTRICAL MIXERS

| Puterea:           | 1800 W       |
|--------------------|--------------|
| Paddle size:       | K3 - Ø120 mm |
| 2 speeds:          |              |
| - Speed I:         | 180-430 rpm  |
| - Speed II         | 300-680 rpm  |
| Connecting rod:    | M14          |
| Adjustable height: | 10 cm        |

### **DZ-SE171**

MORTAR MIXING PADDLE Classification: ACCESSORIES FOR PAINT OR MORTAR

ELECTRIC MIXERS/MIXERS

| Diameter: | 12 cm |
|-----------|-------|
| Length:   | 58 cm |



**DZ-C298** CONSTRUCTION MATERIALS MIXER, 2 PADDLES, 2500W

| Power:             | 2500 W    |  |
|--------------------|-----------|--|
| Maximum speed:     |           |  |
| - Speed I:         | 0-590 rpm |  |
| - Speed II:        | 0-800 rpm |  |
| Paddle diameter:   | 120 mm    |  |
| Connecting system: | M14       |  |



### **DZ-EI103**

SCISSORS FOR PVC PIPES 32MM

Classification: EQUIPMENTS FOR PLUMBERS

37

• Product type: Scissors for polypropylene pipes

| Pipe diameter: | 32 |
|----------------|----|

## 2022

**JIY Products** 





PNEUMATIC PLASTERING MACHINE FOR WALLS, WITH NOZZLES

Classification: PNEUMATIC TOOLS

Nozzles included

### DZ-C224

PNEUMATIC PLASTERING MACHINE FOR CEILINGS, WITH NOZZLES

Classification: PNEUMATIC TOOLS

Nozzles included



DZ-C202 PNEUMATIC PLASTERING MACHINE Classification: PNEUMATIC TOOLS



DZ-EI100 HOT MELT AND SCISSORS PPR 1500W Classification: EQUIPMENTS FOR PLUMBERS



DZ-EI101 HOT MELT AND SCISSORS PPR 600W

Classification: EQUIPMENTS FOR PLUMBERS



DZ-EI102 HOT MELT AND SCISSORS PPR 900W

Classification: EQUIPMENTS FOR PLUMBERS



DZ-EI104 HOT MELT AND SCISSORS PPR 2000W Classification: EQUIPMENTS FOR PLUMBERS

| Working pressure:            | 6 bar (8bar without nozzles) |
|------------------------------|------------------------------|
| Flow:                        | 30-60 mp/h                   |
| Compressor connection socket | 3/8"                         |
|                              |                              |
| size:                        |                              |
| size:<br>Nozzle connection:  | threading                    |

| Working pressure:            | 6 bar (8bar without nozzles) |
|------------------------------|------------------------------|
| Flow:                        | 30-60 mp/h                   |
| Compressor connection socket | 3/8"                         |
| size:                        |                              |
| Nozzle connection:           | threading                    |
| Use:                         | wall plastering              |

| Working pressure:            | 8 bar           |
|------------------------------|-----------------|
| Flow:                        | 30-60mp/h       |
| Compressor connection socket | 3/8"            |
| size:                        |                 |
| Use:                         | wall plastering |

| Power:               | 1500 W              |
|----------------------|---------------------|
| Pipe diameter:       | 20-63 mm            |
| Heating time:        | <15min              |
| Surface temperature: | 0-300°              |
| Included:            | Ø20; Ø25; Ø32; Ø40; |
|                      | Ø50; Ø63            |

| Power:               | 600 W               |
|----------------------|---------------------|
| Pipe diameter:       | 20-63 mm            |
| Heating time:        | <15 min             |
| Surface temperature: | 0-300°              |
| Included:            | Ø20; Ø25; Ø32; Ø40; |
|                      | Ø50; Ø63            |

| Power:               | 900 W               |
|----------------------|---------------------|
| Pipe diameter:       | 20-63 mm            |
| Heating time:        | <15 min             |
| Surface temperature: | 0-300°              |
| Included:            | Ø20; Ø25; Ø32; Ø40; |
|                      | Ø50; Ø63            |

| Power:                       | 2000 W              |
|------------------------------|---------------------|
| Maximum working temperature: | 300°                |
| Gluing type:                 | prin incalzire      |
| Pipe diameter:               | 20mm/25mm/32mm/     |
|                              | 40mm/50mm/63mm      |
| Included:                    | Ø20; Ø25; Ø32; Ø40; |
|                              | Ø50; Ø63            |

**JIY Products** 



DZ-C211 CERAMIC TILE CUTTING

MACHINE 400MM

Classification: CERAMIC TILE CUTTING MACHINES

| Maximum cutting thickness: | 10 mm            |
|----------------------------|------------------|
| Maximum working length:    | 400 mm           |
| Tungsten carbide blades:   | Wolfram          |
| Recommended for:           | parallel cutting |
| Usage regime:              | occasional       |



DZ-C212 CERAMIC TILE CUTTING MACHINE 600MM Classification:

CERAMIC TILE CUTTING MACHINES

| Maximum cutting thickness: | 12 mm            |
|----------------------------|------------------|
| Maximum working length:    | 600 mm           |
| Tungsten carbide blades:   | wolfram          |
| Recommended for:           | parallel cutting |
| Usage regime:              | occasional       |



DZ-C213 PROFESSIONAL CERAMIC TILE CUTTING MACHINE 600MM

Classification: CERAMIC TILE CUTTING MACHINES

| Maximum cutting thickness: | 14 mm                   |
|----------------------------|-------------------------|
| Maximum working length:    | 600 mm                  |
| Tungsten carbide blades:   | Wolfram                 |
| Recommended for:           | linear and angular cuts |
| Usage regime:              | intensive               |



DZ-C214 PROFESSIONAL CERAMIC TILE CUTTING MACHINE 800MM

Classification: CERAMIC TILE CUTTING MACHINES

| Maximum cutting thickness: | 12 mm                   |
|----------------------------|-------------------------|
| Maximum working length:    | 600 mm                  |
| Tungsten carbide blades:   | Wolfram                 |
| Recommended for:           | linear and angular cuts |
| Usage regime:              | intensive               |



DZ-C215 PROFESSIONAL CERAMIC TILE CUTTING MACHINE 1000MM

Classification: CERAMIC TILE CUTTING MACHINES

| Maximum cutting thickness: | 16 mm                   |
|----------------------------|-------------------------|
| Maximum working length:    | 1000 mm                 |
| Tungsten carbide blades:   | Wolfram                 |
| Recommended for:           | linear and angular cuts |
| Usage regime:              | intensive               |



### DZ-C217 PROFESSIONAL CERAMIC TILE CUTTING MACHINE 1200MM

Classification:

CERAMIC TILE CUTTING MACHINES

Tungsten carbide blades (wolfram)Recommended for linear and angular cuts

39

| Maximum cutting thickness: | 16 mm     |
|----------------------------|-----------|
| Maximum working length:    | 1200 mm   |
| Usage regime:              | intensive |





### LARGE FORMAT PORCELAIN **TILES CUTTING CUTTER 3200MM**

Classification: CERAMIC TILE CUTTING MACHINES

 Maximum extensible working length up to 320mm, with additional guides facilitates a straight cut without deviations, progressive separation of the material, reducing the risk of breakage

### **DZ-C225**

CERAMIC PRO CUTTING MACHINES WITH TABLE 600MM

**Classification:** CERAMIC TILE CUTTING MACHINES

 Integrated cutting rollers with bearings for parallel and angled cutting

| Maximum cutting thickness: | 14 mm        |
|----------------------------|--------------|
| Maximum working length:    | 600 mm       |
| Tungsten carbide blades:   | Wolfram      |
| Usage regime:              | intensive    |
| Feet:                      | folding feet |

3200 mm

Wolfra

Cutting lenght:

qsten carbide blade



### **DZ-C226**

CERAMIC TILE CUTTING MACHINE, ANGLED AND PARALLEL 630MM

Classification: CERAMIC TILE CUTTING MACHINES

• Angular cuts from 0 to 45 degrees for parallel and angled cuts

| Maximum cutting thickness: | 14 mm   |
|----------------------------|---------|
| Maximum working length:    | 630 mm  |
| Tungsten carbide blades:   | Wolfram |

**NY Products** 

1020

**DZ-C235** 

**DZ-C289** 

CERAMIC TILE CUTTING MACHINE 450W

MARBLE PRO CUTTING MACHINE 1300W 14000RPM 110MM

**Classification:** CERAMIC TILE CUTTING MACHINES

| Power:           | 1300 W    |
|------------------|-----------|
| Disc diameter:   | 110 mm    |
| Cutting depth:   | 30 mm     |
| Cut depth depth: | 30 mm     |
| Usage regime:    | intensive |





**DZ-C267** CERAMIC TILE CUTTING MACHINE 800W WITH TABLE 620MM

Classification: CERAMIC TILE CUTTING MACHINES

| Power:           | 450 W           |
|------------------|-----------------|
| Maximum speed:   | 2950 rpm        |
| Cutting depth:   | 90° - 34mm      |
| Inclinare masa:  | 0°-45°          |
| Table size:      | 395X385 mm      |
| Disc dimensines: | 180X22.2X2.2 mm |

| Power:                | 800 W               |
|-----------------------|---------------------|
| Dimensiuni masa:      | 890X394 mm          |
| Speed:                | 2950 rpm            |
| Disc diameter:        | 200X25.4X4 mm       |
| Cutting depth:        | 90°-32mm / 45°-28mm |
| Cutting table length: | 620 mm              |



CLIPS FOR TILE LEVELER FOR CERAMIC TILES 100 PCS/ BUC

Classification: ACCESSORIES CERAMIC TILE CUTTING MACHINES

• Product type: Clips for tile leveler

### DZ-C229

TILE LEVELING WEDGE FOR CERAMIC TILES 100 PCS/BUC

Classification: ACCESSORIES CERAMIC TILE CUTTING MACHINES

Product type: Wedge



### DZ-C230 PLIER FOR TILE

LEVELING SYSTEM

Classification: ACCESSORIES CERAMIC TILE CUTTING MACHINES

### DZ-C231

CERAMIC TILE LEVEL ADJUSTING DEVICES 50 PCS/BUC

Classification: ACCESSORIES CERAMIC TILE CUTTING MACHINES

• Use: faience, floor tile, natural stone Product type: Spacers



DZ-C232 CERAMIC TILE LEVEL ADJUSTING SET (PLIERS, WEDGES, CLIPS)

Classification: ACCESSORIES CERAMIC TILE CUTTING MACHINES

• Product type: Leveling kit for ceramic tiles

### DZ-C277

SUCTION CUP FOR CERAMIC TILES 123MM

Classification: ACCESSORIES CERAMIC TILE

### DZ-C216 LAMINATED PARQUET CUTTING MACHINE 10X210MM Classification:

PARQUET CUTTING MACHINE

| Material:  | Plastic |
|------------|---------|
| Thickness: | 2 mm    |

Plastic

Steel


Adjustal

Material:

Material:

Plier type:

Material:



| Maximum cutting thickness: | 12mm                          |
|----------------------------|-------------------------------|
| Maximum working length:    | 210 mm                        |
| Allows angular cutting:    | 0° - 180°                     |
| Precise cutting:           | at 90° because of the retaine |
| Recommended for:           | cutting panels of             |
|                            | laminated parquet             |

# **DIY Products**

## 2022

Plastic/Steel

Product type: Ceramic tile leveling kit



**DZ-C303** PLASTIC SUCTION CAP, SINGLE DRUM, 35 KG

nber of drums: 35 k bacity

35 ko



**DZ-C304** PLASTIC SUCTION CAP, TWO DRUMS, 70 KG



**DZ-C305 3D MULTIFUNCTIONAL** MITRE ANGLE



22

Plastic material

1100 W

Ø30 mm 30-40 mm

30-40 m

mber of drums:

Numar of pieces:

Gauge:

Power:

Cut channel width:

Cut channel depth:

Capacity:

DZ-C306 22 PIECES INSTALATION KIT FOR LAMINATED FLOOR



**DZ-C307** CONTOUR GAUGE, FORMS DUPLICATOR



**DZ-C219** 

DRYWALL GYPSUM AND SOFT MASONRY CHANNEL MACHINE

Classification: CUTTING CHANNEL ELECTRIC MACHINES

• Dust evacuation devi



**DZ-C221** 

CERAMIC TILES AND CONCRETE CHANNEL AND CONCRETE

**Classification:** CUTTING CHANNEL ELECTRIC MACHINES

- Water pump power adapter
- Water supply hoseWater supply mini-pump
- Dust evacuation device

| Power:             | 3200 W        |
|--------------------|---------------|
| Speed:             | 6500 rpm      |
| Disc size:         | 130x20x4.5 mm |
| Cut channel width: | 40 mm         |
| Cut channel depth: | 42 mm         |

**NY Products** 







### **DZ-ES001**

MMA-140 SEMI PROFESIONAL WELDING MACHINE

Classification: INVERTERS/WELDING MACHINES

- Digital display
- HOT START system Anti-Stick function
- Arc Force function
- Turbo function

### **DZ-ES002**

### MMA-160 SUPER POWER WELDING MACHINE

Classification: INVERTERS/WELDING MACHINES

- Digital display
- HOT START system
- Anti-Stick function
- Arc Force function Turbo function

### **DZ-ES009**

**INVERTER MMA + LIFT TIG** SYNEGIC CONTROL

Classification: INVERTERS/WELDING MACHINES

• Welding tip MMA+ Lift TIG Digital display

### **DZ-ES010**

**INVERTER HF TIG +** MMA 285 TORCH

Classification: INVERTERS/WELDING MACHINES

• Welding tip MMA+ HF TIG Digital display

## **DZ-ES011**

**INVERTER ECOCUT 40F2** HF ARC STIKING PLASMA

INVERTERS/WELDING MACHINES

• CUT - better cut, without distortions

| Welding method:             | MMA         |
|-----------------------------|-------------|
| Absorbed power:             | 6.1kVA      |
| Working voltage:            | 25-50V      |
| Electric current intensity: | 20-140A     |
| Welding cables:             | 200A        |
| Electrode size:             | 1.6-3.2mm   |
| Technology:                 | Full Bridge |
| Working cycle:              | 80% - 30°   |
| Efficiency:                 | 95%         |
| Power factor:               | 93%         |

| Welding method:             | MMA         |
|-----------------------------|-------------|
| Absorbed power:             | 6.1kVA      |
| Working voltage:            | 45V         |
| Electric current intensity: | 20-140A     |
| Welding cables:             | 300A        |
| Electrode size:             | 1.6-5mm     |
| Technology:                 | Full Bridge |
| Working cycle:              | 100% - 30°  |
| Efficiency:                 | 95%         |
| Power factor:               | 93%         |

| Welding method:                  | MMA + Lift TIG |
|----------------------------------|----------------|
| Electric current intensity:      | 10-200A        |
| Absorbed power:                  | 6.6kVA         |
| Output voltage without charging: | 70V            |
| Output voltage in load:          | 25.6V          |
| Welding cable:                   | 300A           |
| Working cycle:                   | 50-60%         |
| Power factor:                    | 89%            |
| Efficiency:                      | 85%            |
| Welding wire diameter:           | 0.6mm-1.0mm    |
| Electrode size:                  | 1.6-4.0        |

| Welding method:                  | HF TIG + MMA       |
|----------------------------------|--------------------|
| Electric current intensity:      | 10-285A            |
| Absorbed power:                  | 7.9kVA             |
| Output voltage without charging: | 66V                |
| Output voltage in load:          | TIG 18V/ MMA 27.2V |
| Welding cable:                   | 300A               |
| Working cycle:                   | 50-60%             |
| Power factor:                    | 89%                |
| Efficiency:                      | 85%                |
| Welding wire diameter:           | 0.6mm-1.0mm        |
| Electrode size:                  | 1.6-4.0            |

| Welding method:                  | ECOCUT 40F2 HF ARC |
|----------------------------------|--------------------|
| Electric current intensity:      | 15-40A             |
| Absorbed power:                  | 5.54kVA            |
| Output voltage without charging: | 270V               |
| Output voltage in load:          | 96V                |
| Welding cable:                   | 300A               |
| Working cycle:                   | 50-60%             |
| Power factor:                    | 93%                |
| Efficiency:                      | 85%                |
| Maximum cutting thickness:       | 15mm               |
| Optimum cutting thickness:       | ≤10mm              |

| Glass size:     | 0.98x0.55   |
|-----------------|---|
| Light status:   | DIN4  |
| Dark status:    | DIN5~9/9~13)  |
| Commuting time: | 1/10000S  |
| Come back time: | 0.15/0.45/0.85  |
| Material:       | PP  |
| Supply batteri: | Lithium battery / supplied wi<br>solar energy - 1200mAh |

2022







010300

## **DZ-ES008**

### ADJUSTABLE WELDING HELMET WITH TRUE COLOR VISION

Classification: ACCESSORIES WELDING MACHINES AND INVERTERS

 Battery discharge sensor Interchangeable battery

| ze:        | 0.98x0.55                       |
|------------|---------------------------------|
| atus:      | DIN4                            |
| atus:      | DIN5~9/9~13)                    |
| ting time: | 1/10000S                        |
| ack time:  | 0.1S/0.4S/0.8S                  |
| l:         | PP                              |
| batteri:   | Lithium battery / supplied with |
|            | 1200-11                         |



ANGLE GRINDER 600W 115MM

Classification: ANGLE GRINDERS

Interchangeable handle

| Power:          | 710 W     |
|-----------------|-----------|
| Maximum speed:  | 12000 rpm |
| Disc diameter:  | ø115      |
| Spindle thread: | M14       |

DZ-SE113

ANGLE GRINDER 750W 125MM

Classification: ANGLE GRINDERS

Interchangeable handle

| Power:          | 750 W     |
|-----------------|-----------|
| Maximum speed:  | 12000 rpm |
| Disc diameter:  | ø115      |
| Spindle thread: | M14       |
|                 |           |

·

DZ-SE114

ANGLE GRINDER 1200W 125MM WITH LONG HANDLE

Classification: ANGLE GRINDERS

Interchangeable handle



DZ-SE105 ANGLE GRINDER 800W 125MM Classification:

Classification: ANGLE GRINDERS

| Power:          | 1200 W    |
|-----------------|-----------|
| Maximum speed:  | 12000 rpm |
| Disc diameter:  | ø115      |
| Spindle thread: | M14       |

 Power:
 800W

 Maximum speed:
 12000rpm


 Disc diameter:
 e125 mm

 Spindle thread:
 M14



DZ-SE149 ANGLE GRINDER 720W 125 ON/OFF LATERAL

Classification: ANGLE GRINDERS



2022

**DIY Products** 



DZ-SE150 ANGLE GRINDER 900W 125 ON/OFF LATERAL

Classification: ANGLE GRINDERS

| Maximum speed: 12000 rot/min | ower:           | 900W          |
|------------------------------|-----------------|---------------|
| Disc diameter:               | aximum speed: 1 | 12000 rot/min |
| Disc diameter.               | isc diameter:   | ø125 mm       |

DIY Products

2022

DZ-SE161 ANGLE GRINDER

115MM 500W HOBBY

| Power:         | 500 W     |
|----------------|-----------|
| Speed:         | 12000 rpm |
| Disc diameter: | ø115 mm   |

Classification: ANGLE GRINDERS



### DZ-SE160

POLIZOR UNGHIULAR 125MM 900W TOP

Classification: ANGLE GRINDERS

| Power:     |      | 900 W     |
|------------|------|-----------|
| Speed:     |      | 12000 rpm |
| Disc diame | ter: | ø125 mm   |



### **DZ-SE158**

POLIZOR UNGHIULAR 230MM 2000W

Classification: ANGLE GRINDERS

**DZ-SE159** 

POLIZOR UNGHIULAR 230MM 2350W Classification: ANGLE GRINDERS

| _              |          |
|----------------|----------|
| Power:         | 2000 W   |
| Speed:         | 6500 rpm |
| Disc diameter: | ø230 mm  |

| Power:         | 2350 W   |
|----------------|----------|
| Speed:         | 6300 rpm |
| Disc diameter: | ø230 mm  |



### DZ-SE222

ANGLE GRINDER SUPPORT, Ø60MM Classification: ACCESSORIES ANGLE GRINDERS

Compatible: Angle grinder

| Size:                | 19X23.5X28 cm |
|----------------------|---------------|
| Frame material:      | Aluminum      |
| Base plate material: | Fonta         |
| Cutting depth:       | 30 mm         |
| Column height:       | 40 cm         |
| Cursa maxima:        | 60 mm         |



WORKTOP GRINDER 150W 6" MD3215

Classification: WORKTOP ELECTRIC GRINDER

• Used for cutting, polishing, sharpening and removing excess metal and smoothing metal surfaces.




### **DZ-SE139**

### WORKTOP GRINDER 250W 6" MD3215S

Classification: WORKTOP ELECTRIC GRINDER

• Used for cutting, polishing, sharpening and removing excess metal and smoothing metal surfaces.



150 W

3450 rpm

ø150x16x12.7 m

Power:

Speed: Grinder stone size

# **JIY Products**

2022




### **DZ-SE140**

### WORKTOP GRINDER 350W 8" MD3220S

Classification: WORKTOP ELECTRIC GRINDER

 Used for cutting, polishing, sharpening and removing excess metal and smoothing metal surfaces.



## ...

### **DZ-SE169**

GRINDING STONE 150X16X12.7 FOR DZ-SE138, DZ-SE139

Classification: ACCESSORIES WORKTOP ELECTRIC GRINDER Diameter: 150mm Thickness: 12.7 mm

### **DZ-SE170**

GRINDING STONE 200X20X12.7 FOR DZ-SE140

Classification: ACCESSORIES WORKTOP ELECTRIC GRINDER

| Diameter:  | 200 mm  |
|------------|---------|
| Thickness: | 12.7 mm |



DZ-C278 DIAMOND DISC SEGMENTED 125X22.2X7MM Classification: ACCESSORIES ANGLE GRINDERS

| Thickness:      | 1.2 mm        |
|-----------------|---------------|
| Outer diameter: | 125 mm        |
| Inner diameter: | 22.2 mm       |
| Compatible:     | Angle grinder |
| Segment height: | 7 mm          |
| Product type:   | Diamond disc  |
| Toothing:       | Segmented     |

DZ-C279 DIAMOND DISC SEGMENTED 230X25.4X7MM

Classification: ACCESSORIES ANGLE GRINDERS

| Thickness:      | 1.8 mm        |
|-----------------|---------------|
| Outer diameter: | 230 mm        |
| Inner diameter: | 25.4 mm       |
| Compatible:     | Angle grinder |
| Segment height: | 7 mm          |
| Product type:   | Diamond disc  |
| Toothing:       | Segmented     |



DZ-C280 DIAMOND DISCTURBO 125X22.2X7MM Classification: ACCESSORIES ANGLE GRINDERS

| Thickness:      | 1.2 mm        |
|-----------------|---------------|
| Outer diameter: | 125 mm        |
| Inner diameter: | 22.2 mm       |
| Compatible:     | Angle grinder |
| Segment height: | 7 mm          |
| Product type:   | Diamond disc  |
| Toothing:       | Continuous    |



DZ-C281 DIAMOND DISC TURBO 230X25.4X7MM Classification: ACCESSORIES ANGLE GRINDERS

**DZ-C282** 

125X22.2X7MM

| Thickness:      | 1.8 mm        |
|-----------------|---------------|
| Outer diameter: | 230 mm        |
| Inner diameter: | 25.4 mm       |
| Compatible:     | Angle grinder |
| Segment height: | 7 mm          |
| Product type:   | Diamond disc  |
| Toothing:       | Continuous    |

| Thickness:      | 1.2 mm        |
|-----------------|---------------|
| Outer diameter: | 125 mm        |
| Inner diameter: | 22.2 mm       |
| Compatible:     | Angle grinder |
| Segment height: | 7 mm          |
| Product type:   | Diamond disc  |
| Toothing:       | Continuous    |

DZ-C283 DIAMOND DISC UNIVERSAL 230X25.4X7MM Classification: ACCESSORIES ANGLE GRINDERS

DIAMOND DISC UNIVERSAL

Classification: ACCESSORIES ANGLE GRINDERS

| Thickness:      | 1.8 mm        |
|-----------------|---------------|
| Outer diameter: | 230 mm        |
| Inner diameter: | 25.4 mm       |
| Compatible:     | Angle grinder |
| Segment height: | 7 mm          |
| Product type:   | Diamond disc  |
| Toothing:       | Continuous    |



DZ-C284 DIAMOND DISC FOR CERAMICS 110X22.2X1.6X10MM Classification: ACCESSORIES ANGLE GRINDERS

| 0.8 mm        |
|---------------|
| 110 mm        |
| 22.2 mm       |
| Angle grinder |
| 10 mm         |
| Continuous    |
| Diamond disc  |
| Mn 65         |
| Ceramic tiles |
|               |

| <b>(</b> |  |
|----------|--|
| C        |  |
| C        |  |
| <b>(</b> |  |



ROTARY HAMMER 600W, 2.2J

Classification: ROTARY HAMMERS

Chuck SDS Plus

| Power:                        | 600 W           |
|-------------------------------|-----------------|
| Speed:                        | 0-870 rpm       |
| Number of percussions/minute: | 0-4800 bpm      |
| Drilling maximum diameter:    | - masonry: Ø26; |
|                               | - wood: Ø30;    |
|                               | - metal: Ø13    |
| Impact energy:                | 2.2 J           |



DZ-SE175 ROTARY HAMMER 900W 850RPM 26MM

Classification: ROTARY HAMMERS

Chuck SDS Plus

| Power:                | 900 W   |
|-----------------------|---------|
| Maximum speed:        | 850 rpm |
| Rated drilling range: | 6-26 mm |
| Percussion:           | Yes     |
| Chuck type:           | SDS     |
| Impact energy:        | 4 J     |



DZ-SE118 ROTARY HAMMER 1500W

Classification: ROTARY HAMMERS

• Interchangeable self-tightening chuck for quick transition from percussion drilling in concrete to drilling without percussion in wood or metal.

| Power:                     | 1500 W        |
|----------------------------|---------------|
| Maximum speed:             | 800 rpm       |
| Drilling maximum diameter: | - steel: Ø13; |
|                            | - wod: Ø40;   |
|                            | - stone: Ø26  |
| Numar of gears:            | 6             |
| Impact energy:             | 5 J           |



DZ-SE176

ROTARY HAMMER 1500W 930RPM 4500BPM 32MM

Classification: ROTARY HAMMERS

| Power:                   | 1500W    |
|--------------------------|----------|
| Maximum speed:           | 930 rpm  |
| Frequency maxima impact: | 4500 bpm |
| Speeds:                  | 5        |
| Percussion:              | Yes      |
| Rated drilling range:    | 6-32 mm  |
| Impact energy:           | 5 J      |

# **DIY Products**



### DZ-C290 TABLE SAW

600W

| Power:         | 600 W                 |
|----------------|-----------------------|
| Maximum speed: | 2950 rpm              |
| Table size:    | 500X335 mm            |
| Table tilt:    | 0-45°                 |
| Cutting depth: | 90°-45 mm / 45°-27 mm |
| Disc size:     | 200X16X2.5 mm         |



### DZ-SE131 ROTARY HAMMER

800W, 3.0J

Classification: ROTARY HAMMERS • Chuck SDS Plus

Rapid chuck with thread

| Power:                        | 800 W          |
|-------------------------------|----------------|
| Maximum speed:                | 0-1100 rpm     |
| Impact energy:                | 3J             |
| Number of percussions/minute: | 0-4000 bpm     |
| Drilling maximum diameter:    | - masory: Ø26; |
|                               | - wood: Ø30;   |
|                               | - metal: Ø13   |



| Power:                    | 1200 W   |
|---------------------------|----------|
| Impact energy:            | 15 J     |
| Frequency de impact:      | 3900 bmp |
| Distance between centers: | 1000 mm  |
| Centers height:           | 173 mm   |
| Rotor:                    | Ø 44     |
| Stator:                   | Ø 72     |





### **DZ-SE163**

DEMOLITION HAMMER 1600W 1500BPM 45J Clasificare: DRILL AND SCREWDRIVER MACHINES

| Power:                    | 1600 W   |
|---------------------------|----------|
| Impact energy:            | 45 J     |
| Frequency de impact:      | 1500 bpm |
| Distance between centers: | 1000 mm  |
| Centers height:           | 173 mm   |
| Rotor:                    | Ø 53     |
| Stator:                   | Ø 94     |

### DZ-C255

GASOLINE DEMOLITION HAMMER 2 STROKE 52CC 20-55J 1500BPM

Classification: DRILL AND SCREWDRIVER MACHINES

| Tip motor:     | 2 stroke engine, monocilinder |
|----------------|-------------------------------|
| Power kW/W:    | 1790 W                        |
| Power HP:      | 2.4 CP                        |
| Impact energy: | 20-55 J                       |
| Impact rate:   | 700-1500 bpm                  |
| Max. torque:   | 3.5 Nm                        |
| Displacement:  | 52cc                          |
| Maximum speed: | 6500 rpm                      |
| Starting:      | rope                          |
| Fuel:          | Gasoline                      |



ELECTRIC CIRCULAR SAW 480W 85MM

Classification: HAND ELECTRIC CIRCULAR SAWS

Parallel guideLaser guidance for tracing

| Power:         | 480 W                  |
|----------------|------------------------|
| Maximum speed: | 3500 rpm               |
| Disc:          | Ø 85mm x 10mm          |
| Cutting depth: | - wood - 27mm;         |
|                | - ceramic tiles - 8mm; |
|                | - Aluminum - 3mm       |



### DZ-SE100

CIRCULAR SAW 1200W 185MM Classification: HAND ELECTRIC CIRCULAR SAWS

Parallel guide
Angle cutting

|   | 4        | STIS            | F  |   |
|---|----------|-----------------|----|---|
| 4 | PETC     | POLZ<br>NT HORY |    |   |
| - |          | 1               | P2 | 1 |
|   | Sites av | 2er<br>M        |    |   |

**DIY Products** 

2022

### DZ-SE151

ELECTRIC CIRCULAR SAW 1500W 185MM

Classification: HAND ELECTRIC CIRCULAR SAWS

Parallel guidanceAngle cutting

Suction adapter

| Power:                 | 1200 W            |
|------------------------|-------------------|
| Maximum speed:         | 5800 rpm          |
| Disc size:             | Ø185 (7-1/4") 24T |
| Maximum cutting depth: | - 90° - 62 mm     |
|                        | - 45° - 46 mm     |

| Power:                       | 1500 W                     |
|------------------------------|----------------------------|
| Network protection required: | 12 A                       |
| Speed:                       | 5500 rpm                   |
| Disc size:                   | Ø185 (7-1/4")              |
| Wood cutting depth:          | - 62mm at an angle of 90°; |
|                              | - 46mm at an angle of 45°  |



### DZ-SE152

ELECTRIC CIRCULAR SAW 1800W 185MM

Classification: HAND ELECTRIC CIRCULAR SAWS

Parallel guidanceAngle cutting

Suction adapter

| Power:                       | 1800 W                     |
|------------------------------|----------------------------|
| Network protection required: | 15 A                       |
| Speed:                       | 5800 rpm                   |
| Disc size:                   | Ø185 (7-1/4")              |
| Wood cutting depth:          | - 62mm at an angle of 90°; |
|                              | - 46mm at an angle of 45°  |

### **DZ-SE106**

STATIONARY ELECTRIC CIRCULAR SAW 1400W 210MM

Classification: STATIONARY ELECTRIC CIRCULAR SAWS

Rotary table with angle adjustment and pivoting disc
Angle cutting

| Power:             | 1400 W         |
|--------------------|----------------|
| Maximum speed:     | 5000 rpm       |
| Cutting disc size: | Ø210 mm        |
| Cutting speed:     | 55 m/s         |
| Guidance laser:    | 650 nm; < 1 mW |



VERTICAL SAW WITH BAND 230W

Classification: ELECTRIC SAWS

| Power:                | 230 W        |
|-----------------------|--------------|
| Speed:                | 680 rpm      |
| Cutting wire length:  | 1511 mm      |
| Work table width:     | 230 mm       |
| Table size:           | 300 x 300 mm |
| Table tilt:           | 0-45°        |
| Dust extraction hole: | 30/40        |



### DZ-SE103

PENDULAR SAW 600W 80MM

Classification: VERTICAL PENDULAR ELECTRIC SAWS

Variable speedDust blowing system

| Power:              | 600 W      |
|---------------------|------------|
| Maximum speed:      | 0-3000 rpm |
| Cutting blade size: | 80 mm      |



### DZ-SE102 RECIPROCATING SAW

710W 115MM

Classification: VERTICAL PENDULAR ELECTRIC SAWS

| Power:         | 710 W           |
|----------------|-----------------|
| Maximum speed: | 0-2800 rpm      |
| Cutting depth: | - wood - 115mm; |
|                | - steel - 6mm   |
| Stroke length: | 20 mm           |

DZ-C236 CIRCULAR SAW WITH TABLE FOR WOOD 1800W

Classification: ELECTRIC SAWS

| Power:            | 1800 W           |
|-------------------|------------------|
| Speed:            | 5700 rpm         |
| Cutting depth:    | 73mm - angle 90° |
|                   | 48mm - angle 45° |
| Table height:     | 850 mm           |
| Table extension:  | 640 x 250 mm     |
| Table dimensions: | 640 x 445 mm     |
| Disc diameter:    | 250 mm           |



DZ-SE223 METAL CUT OFF MACHINE 2200W 3900RPM

Classification: HAND ELECTRIC CIRCULAR SAWS

| Power:                 | 2200 W        |
|------------------------|---------------|
| Speed:                 | 3900 rpm      |
| Cutting type:          | right/angled  |
| Cutting disc diameter: | 355X25.4X3 mm |



### DZ-SE217 STATIONARY ELECTRIC

CIRCULAR SAW 2600W 4200RPM

Classification: STATIONARY ELECTRIC CIRCULAR SAWS

51

• Angle cutting 0-45°

| Power:          | 2600 W   |
|-----------------|----------|
| Turatie maxim:  | 4200 rpm |
| Outer diameter: | 355 mm   |
| Inner diameter: | 25.4 mm  |
| Angle:          | 0-45°    |

# DIY Products



### DZ-SE104 PENDULAR SAW 450W 55MM

Classification: VERTICAL PENDULAR ELECTRIC SAWS

| Product type:       | Fierastrau pendular |
|---------------------|---------------------|
| Power:              | 450 W               |
| Maximum speed:      | 0-3000 rpm          |
| Cutting blade size: | 55mm                |
| Cutting depth:      | - wood - 115mm;     |
|                     | - steel - 6mm       |
| Stroke length:      | 17 mm               |



DZ-SE219 PENDULAR SAW 710W 80MM

| Product type:       | Pendular saw          |
|---------------------|-----------------------|
| Power:              | 710 W                 |
| Maximum speed:      | 3000 rpm              |
| Base sole material: | Aluminum              |
| Cutting capacity:   | wood 80mm / metal 8mm |



**DZ-SE153** 

RECIPROCATING SAW 900W 150MM Classification: ELECTRIC PENDULAR SAWS

| Product type:           | Reciprocating saw |
|-------------------------|-------------------|
| Power:                  | 900 W             |
| Speed:                  | 2800 rpm          |
| Stroke length:          | 28 mm             |
| Maximum wood thickness: | 150 mm            |

DIY Products



DZ-SE178 RECIPROCATING SAW 1050W 300MM

Classification: ELECTRIC PENDULAR SAWS

| Product type:      | Reciprocating saw      |
|--------------------|------------------------|
| Power:             | 1050 W                 |
| Maximum speed:     | 3000 rot/min           |
| Stroke length:     | 25 mm                  |
| Speed:             | 6                      |
| Cutting thickness: | wood-300mm/ metal-20mm |



DRILL WITH BATTERY 12V LI-ION

Classification: DRILL AND SCREWDRIVER MACHINES WITH BATTERY

• Contains battery and charger LED for lighting the work area

| Power supply:     | Battery  |
|-------------------|----------|
| Battery capacity: | 1.3 Ah   |
| Battery voltage:  | 12 V     |
| 2 speeds:         |          |
| - speed I:        | 350 rpm  |
| - speed II:       | 1300 rpm |
| Torque:           | 23 Nm    |



### **DZ-SE110**

**DRILL WITH BATTERY** 14.4V LI-ION

Classification: DRILL AND SCREWDRIVER MACHINES WITH BATTERY

• Contains battery and charger LED for lighting the work area

| Power supply:     | Battery    |
|-------------------|------------|
| Battery capacity: | 1.3 Ah     |
| Battery voltage:  | 14.4 V     |
| 2 speeds:         |            |
| - speed I:        | 0-450 rpm  |
| - speed II:       | 0-1550 rpm |
| Torque:           | 28 Nm      |

18V

### **DZ-SE111**

**DRILL WITH BATTERY** WITH BATTERY 18V LI-ION

Classification: DRILL AND SCREWDRIVER MACHINES WITH BATTERY

• Contains battery and charger LED for lighting the work area

| Power supply:     | Battery    |
|-------------------|------------|
| Battery capacity: | 1.3 Ah     |
| Battery voltage:  | 18 V       |
| 2 speeds:         |            |
| - speed I:        | 0-450 rpm  |
| - speed II:       | 0-1550 rpm |
| Torque:           | 30Nm       |

**JIY Products** 



## **DZ-SE115**

IMPACT DRILL 600W (DRILL)

**Classification:** ELECTRIC DRILL AND SCREWDRIVER MACHINES

Adjustable height limiter

Lock button

• Variable speed drive

| Power supply:              | Cable           |
|----------------------------|-----------------|
| Power:                     | 600 W           |
| Maximum speed:             | 2800 rpm        |
| Maximum drilling diameter: | - steel: Ø13;   |
|                            | - wood: Ø 25;   |
|                            | - concrete: Ø16 |

## **DZ-SE116**

IMPACT DRILL 810W (DRILL)

**Classification:** ELECTRIC DRILL AND SCREWDRIVER MACHINES

Adjustable height limiter

 Lock button • Variable speed drive

| Power supply:              | Cable           |
|----------------------------|-----------------|
| Power:                     | 810 W           |
| Maximum speed:             | 2800 rpm        |
| Maximum drilling diameter: | - steel: Ø13;   |
|                            | - wood: Ø 25;   |
|                            | - concrete: Ø16 |



IMPACT DRILL 910W (DRILL)

Classification: ELECTRIC DRILL AND SCREWDRIVER MACHINES

Adjustable height limiter
Lock button

Variable speed drive




### **DZ-SE154**

IMPACT DRILL 600W POWER 4.5A

Classification: ELECTRIC DRILL AND SCREWDRIVER MACHINES

| Power supply:              | Cable           |
|----------------------------|-----------------|
| Power:                     | 910 W           |
| Voltage:                   | 220 V           |
| Slow speed:                | 2800 rpm        |
| Maximum drilling diameter: | - steel: Ø13;   |
|                            | - wood: Ø 20;   |
|                            | - concrete: Ø13 |



# DIY Products

2022



### **DZ-SE155**

IMPACT DRILL 710W POWER 6A

Classification: ELECTRIC DRILL AND SCREWDRIVER MACHINES

| Power supply:   | Cable    |
|-----------------|----------|
| Power:          | 710 W    |
| Voltage:        | 220 V    |
| Speed:          | 3000 rpm |
| Chuck diameter: | 13 mm    |

DZ-SE157 IMPACT DRILL 1050W 2 SPEEDS

Classification: ELECTRIC DRILL AND SCREWDRIVER MACHINES

Chuck with key

| Power supply:                  | Cable     |
|--------------------------------|-----------|
| Power:                         | 1050 W    |
| Voltage:                       | 220 V     |
| Maximum speed:                 | 2800 rpm  |
| Maximum number of percussions: | 44800 bpm |



### DZ-SE127

DRILL2 BATTERIES LI-ION 18V

Classification: DRILL AND SCREWDRIVER MACHINES WITH BATTERY

Contains batteries 2 pcs
Work area LED lighting

| Power supply:           | Battery        |
|-------------------------|----------------|
| Battery capacity:       | 1.3 Ah         |
| Battery voltage:        | 18 V           |
| Percussion beats / min: | 0-21750 bpm    |
| Maximum torque:         | 30 Nm          |
| Hole diameter:          | - wood: 38 mm; |
|                         | - steel: 13 mm |
| 2 speeds:               |                |
| - Driving speed I:      | 0-400 rpm      |
| - Speed II:             | 0-1450 rpm     |



WITH BATTERY

IMPACT DRILL 2 BATTERIES LI-ION 18V Classification: DRILL AND SCREWDRIVER MACHINES

Contains batteries 2 pcs
Work area LED lighting

| Power supply:     | Battery        |
|-------------------|----------------|
| Battery voltage:  | 1.3 Ah         |
| Battery capacity: | 18 V           |
| Maximum torque:   | 30 Nm          |
| Hole diameter:    | - wood: 38 mm; |
|                   | - steel: 13 mm |
| 2 speeds          |                |
| - Speed I:        | 0-400 rpm      |
| - Speed II        | 0-1450 rpm     |



### DZ-SE172

WOOD SPLIT 32 MM FOR IMPACT DRILL

Classification: ACCESSORIES FOR DRILLS

| Diameter:  | 32 mm |
|------------|-------|
| Material:  | Steel |
| Head type: | Round |



### DZ-SE173 WOOD SPLIT 42 MM FOR IMPACT DRILL

Classification: ACCESSORIES FOR DRILLS

| Diameter:  | 42 mm |
|------------|-------|
| Material:  | Steel |
| Head type: | Round |



DZ-SE174 WOOD SPLIT 45 MM FOR IMPACT DRILL

Classification: ACCESSORIES FOR DRILLS

| Diameter:  | 45 mm |
|------------|-------|
| Material:  | Steel |
| Head type: | Round |



## DZ-SE141

BATTERY 20V/4AH

Classification: BATTERIES AND CHARGERS FOR ELECTRIC TOOLS

• Compatible with the models DZ-SE129, DZ-SE132, DZ-SE133, DZ-SE134, DZ-SE135, DZ-SE137

| Battery capacity: | 4 Ah |  |
|-------------------|------|--|
| Battery Voltage:  | 20 V |  |



SCREW BAND FOR DZ-SE137

Classification: CONSUMABILE MASINI DE GAURIT


Compatibility: Drill with band DZ-SE137



DZ-SE220 ELECTRIC DRILL STAND, Ø60MM, 400MM

Classification: ACCESSORIES FOR DRILLS

Compatible: Drill



DZ-SE137

Compatible with:



### **DZ-SE221**

ADJUSTABLE DRILL STAND, Ø60MM, 290MM Classification: ACCESSORIES FOR DRILLS

Compatible: Drill

| Size:                      | 23X13X29 cm |
|----------------------------|-------------|
| Base plate material:       | Aluminum    |
| Column height:             | 29 cm       |
| Maximum drilling depth:    | 60 mm       |
| Maximum clamping aperture: | 60 mm       |




DZ-SE233 3 PCS/SET DRILL

BRUSH HEAD Classification:

ACCESSORIES FOR DRILLS

• Compatible: Drill



2022

DIY Products



DZ-SE234 4 PCS/SET DRILL BRUSH HEAD Classification: ACCESSORIES FOR DRILLS

Compatible: Drill

| Numar perii:         | 4       |
|----------------------|---------|
| Unealta compatibila: | Drill   |
| Material perie:      | Plastic |



### DZ-SE122 PAINT GUN

HVLP 350W

Classification: HOT AIR AND SPAYING HAND-HELD ELECTRIC GUNS

| Power:                | 350 W            |
|-----------------------|------------------|
| Tank capacity:        | 700 ml           |
| Frequency:            | 50 Hz            |
| Sound pressure level: | LpA 76.13 dB (A) |
| Maximum viscosity:    | DIN-s            |

### DZ-SE143

HAND-HELD SPRAY ELECTRIC GUN 350W 1000ML/MIN

Classification: HOT AIR AND SPAYING HAND-HELD ELECTRIC GUNS

| Power:             | 400 W               |
|--------------------|---------------------|
| Tank capacity:     | 1000 ml             |
| Flow:              | 920-1000 ml/min     |
| Pressure:          | 144 mbar (14.4 kPa) |
| Nozzles included:  | 1.8/2.2/2.6 mm      |
| Maximum viscosity: | 60 DIN-s            |



### DZ-SE144

HAND-HELD SPRAY ELECTRIC GUN 600W 1200ML/MIN

Classification: HOT AIR AND SPAYING HAND-HELD ELECTRIC GUNS

| Power:             | 600 W               |
|--------------------|---------------------|
| Tank capacity:     | 1000 ml             |
| Flow:              | 920-1000 ml/min     |
| Pressure:          | 144 mbar (14.4 kPa) |
| Nozzles included:  | 1.8/2.2/2.6/1.5 mm  |
| Maximum viscosity: | 100 DIN-s           |



### **DZ-SE180**

ELECTRIC HAND-HELD SPRAY GUN 650W WITH COMPRESSOR

Classification: ELECTRIC HAND-HELD SPRAY GUN

| Power:             | 650 W     |
|--------------------|-----------|
| Material:          | Plastic   |
| Tank capacity:     | 800 ml    |
| Speed:             | 32000 rpm |
| Nozzle diameter:   | 2.6 mm    |
| Hose length:       | 1.3 m     |
| Maximum viscosity: | 130 DIN-s |

**DZ-SE145** 

HAND-HELD HOT AIR ELECTRIC GUN 2 STEPS 600 C

Classification: HOT AIR AND SPAYING HAND-HELD ELECTRIC GUNS

| Power:              | 2000 W    |
|---------------------|-----------|
| Air flow:           |           |
| - step I:           | 300I/min  |
| - step II:          | 5001/min  |
| Temperature stages: |           |
| - step l:           | 0-450°C   |
| - step II:          | 450-600°C |
|                     |           |



DZ-SE146

HAND-HELD HOT AIR ELECTRIC GUN 3 STEPS 600 C

Classification: HOT AIR AND SPAYING HAND-HELD ELECTRIC GUNS

• 7-steps temperature adjustment display

| Power:              | 2000 W   |
|---------------------|----------|
| Air flow:           |          |
| - step I:           | 2501/min |
| - step II:          | 2501/min |
| - step III:         | 500I/min |
| Temperature stages: |          |
| - step I:           | 0-50°C   |
| - step II:          | 50-450°C |
| - step III:         | 90-600°C |



### DZ-SE123

SOLDERING GUN 100W Classification: STATIONS AND SOLDERING GUNS

57

| Power:            | 100 W                        |
|-------------------|------------------------------|
| Pasting:          | <450°C                       |
| Soldering alloys: | typical melting temperatures |
|                   | of 200°C                     |



SAWDUST COLLECTOR 1150 MC/H

Classification: CUTTING AND WOOD PROCESSING MACHINES

• Separate fine dust from wood residues after processing.

| Power:                   | 550 W     |
|--------------------------|-----------|
| Speed:                   | 2850 rpm  |
| Flow:                    | 1150 mc/h |
| Volume:                  | 65 L      |
| Suction nozzle diameter: | 100 mm    |



### DZ-C239

DUST AND SAWDUST COLLECTOR 1100W

Classification: CUTTING AND WOOD PROCESSING MACHINES

| Power:      | 1100 W            |
|-------------|-------------------|
| Speed:      | 20000 rpm         |
| Flow:       | 183 mc/h          |
| Volume:     | 50 L              |
| Aspiration: | 25 kPa / 250 mbar |



DZ-C240 WOOD PROCESSING ELECTRIC LATHE 350W

| Power:                      | 370W           |
|-----------------------------|----------------|
| Speed:                      | 720 - 2150 rpm |
| Maximum workpiece diameter: | 350mm          |
| Distance between centers:   | 1000 mm        |
| Center height:              | 173 mm         |
| Number of speeds:           | 4              |



DZ-C241

**DZ-C253** 

Classification: CUTTING AND WOOD PROCESSING MACHINES

POWERFUL ELECTRIC ROUTER 26000RPM 1500W

WOOD PROCESSING ELECTRIC LATHE 550W COPYING FUNCTION

Copy function accessory

|   | Power:                      | 550W           |
|---|-----------------------------|----------------|
|   | Speed:                      | 600 - 2200 rpm |
| N | Maximum workpiece diameter: | 350mm          |
|   | Distance between centers:   | 1000 mm        |
|   | Center height:              | 173 mm         |





**JIY Products** 



DZ-SE177 ELECTRIC PLANER 810W

16500RPM 82MM

Classification: ELECTRIC SANDER WITH BAND

| Power:                      | 1500 W          |
|-----------------------------|-----------------|
| Speed:                      | 12000-26000 rpm |
| Maximum milling depth:      | 40 mm           |
| Compatible milling cutters: | 6 mm/8 mm/12 mm |

| Power:                 | 810 W     |
|------------------------|-----------|
| Maximum speed:         | 16500 rpm |
| Maximum planing depth: | 3 mm      |
| Planing width:         | 82 mm     |
| Maximum crease depth:  | 11 mm     |



CONCRETE VIBRATOR, 850W Classification: CONCERETE VIBRATORS

| Power:                 | 850W     |
|------------------------|----------|
| Maximum speed:         | 4000 rpm |
| Maximum hose diameter: | 38mm     |
| Maximum hose length:   | 3m       |
| Noise level:           | 120 dB   |



DZ-C300 CONCRETE VIBRATOR, 1200W Classification: CONCERETE VIBRATORS

| Putere:                | 1200W    |
|------------------------|----------|
| Turatie Relanti:       | 4000 rpm |
| Diametru maxim furtun: | 38mm     |
| Lungime maxima furtun: | 5m       |
| Nivel zgomot:          | 120dB    |

### **DZ-C301** SHAFT FOR CONCRETE

VIBRATOR 1.5MX35MM

Classification: CONCERETE VIBRATORS

| Diameter: | 35 mm |
|-----------|-------|
| Length:   | 1.5 m |

### DZ-C302

SHAFT FOR CONCRETE VIBRATOR 02MX35MM CI C(

| lassification:     |  |
|--------------------|--|
| ONCERETE VIBRATORS |  |

| Diameter: | 35 mm |
|-----------|-------|
| Length:   | 2 m   |





ELECTRIC HOIST (MARACA) 250KG 450W FIR 3MM

Classification: ELECTRIC CRANES

\*The DZ-C264 support is purchased separately.

| Power:           | 450 W                |
|------------------|----------------------|
| Task:            | 250kg-6m / 125kg-12m |
| Lifting speed:   | 4m/min - 250kg /     |
|                  | 8m/min - 125kg       |
| Cable diameter:  | 3 mm                 |
| Body material:   | Steel                |
| Engine material: | Aluminum             |
|                  |                      |



### DZ-C263

ELECTRIC HOIST (MARACA) 500KG 800W FIR 4MM

Classification: ELECTRIC CRANES

\*The DZ-C264 support is purchased separately.

| Power:           | Putere 800 W         |
|------------------|----------------------|
| Task:            | 500kg-6m / 250kg-12m |
| Lifting speed:   | 4m/min - 500kg /     |
|                  | 8m/min - 250kg       |
| Cable diameter:  | 4 mm                 |
| Body material:   | Steel                |
| Engine material: | Aluminum             |



DZ-C264

PIVOT BRACKET FOR ELECTRIC WINCH (CRANE) Classification: ACCESSORIES FOR CRANES

| Material:       | Steel           |
|-----------------|-----------------|
| Pivoting range: | 750mm - 600kg / |
|                 | 1100 mm - 300kg |



DZ-C266

• Oil-free compressor

COMPRESSOR WITHOUT OIL 650W, 9L

Classification: COMPRESSORS AND ACCESSORIES

• Quick faults for air installation (hoses)

 Power:
 1500W

 Flow:
 135 l/min

 Tank capacity:
 30l

 Speed:
 2800 rpm

 Tank dimensions:
 240X420 mm

2022



### DZ-C265

COMPRESSOR WITHOUT OIL 1500W, 30L

Classification: COMPRESSORS AND ACCESSORIES

Oil-free compressorQuick faults for air installation (hoses)

| Power:           | 880W       |
|------------------|------------|
| Flow:            | 80 l/min   |
| Tank capacity:   | 91         |
| Speed:           | 2800 rpm   |
| Tank dimensions: | 160X360 mm |



PORTABLE SMARTER MULTI FUNCTIONAL STARTER 14000MA

Classification: VEHICLE CHARGING ROBOT

| Capacity:                  | 14000 mAH     |
|----------------------------|---------------|
| Input current:             | 1.5V / 0.4A   |
| Output current:            | 5V/1A/2A      |
| Compressor output current: | 12V/8.3A/100W |
| Charging time:             | 8h            |



### DZ-C203

LASER TELEMETER MS-40A

Classification: TELEMETERS

| Measuring range:   | 0.05-40m                           |
|--------------------|------------------------------------|
| Precision:         | ± 1.5mm (1/16 inch)                |
| Measurement units: | m / in / ft                        |
| Laser type:        | 635 nm, <1MW                       |
| Lifetime:          | more than 1 million times          |
| Measuring:         | unique, continuous                 |
| Measurement type:  | aria, volume, indirect, Pythagoras |



### DZ-C204

LASER TELEMETER MS-60A

Classification: TELEMETERS

| Measuring range:   | 0.05-60m                          |
|--------------------|-----------------------------------|
| Precision:         | ± 1.5mm (1/16 inch)               |
| Measurement units: | m / in / ft                       |
| Laser type:        | 635 nm, <1MW                      |
| Lifetime:          | more than 1 million times         |
| Measuring:         | unique, continuous                |
| Measurement type:  | aria, volume, indirect, Pythagora |

022



### **DZ-SE231**

SET OF 3 HSS + TI STEP MILLING CUTTERS 4-12,4-20,4-32MM

Classification: ACCESSORIES FOR DRILLING AND SCREWING MACHINES

| Diameter:        | 2.4mm; 20.4mm; 32mm |
|------------------|---------------------|
| Product type:    | accessories         |
| Compatible tool: | Drilling machine    |

### **DZ-SE232**

SET OF 4 HSS + TI STEP MILLING 8-20, 4-12,12.4 ,6MM

Classification: ACCESSORIES FOR DRILLING AND SCREWING MACHINES

| Diameter:        | 8-20 mm; 4-12 mm;<br>12.4 mm; 6 mm |
|------------------|------------------------------------|
| Product type:    | accessories                        |
| Compatible tool: | Drilling machine                   |



### DZ-C291

ROLL FOR DZ-C211, 212

Classification: ACCESSORIES FOR DRILLING AND SCREWING MACHINES

| Material:        | Tungsten carbide |  |
|------------------|------------------|--|
| Compatible tool: | DZ-C211, DZ-C212 |  |
| Dimensions:      | 15 x 6 x 1.5 mm  |  |




### DZ-C292

ROLL FOR DZ-C214, 215, 217, 225, 227

Classification: ACCESSORIES FOR DRILLING AND SCREWING MACHINES

| Material:        | Tungsten carbide           |
|------------------|----------------------------|
| Compatible tool: | DZ-C214, DZ-C215, DZ-C217, |
|                  | DZ-C225, DZ-C227           |
| Dimensions:      | 22 x 6 x 6 mm              |



### DZ-C293

ROLL FOR DZ-C226

Classification: ACCESSORIES FOR DRILLING AND SCREWING MACHINES

| Material:        | Tungsten carbide |
|------------------|------------------|
| Compatible tool: | DZ-C226          |
| Dimensions:      | 12.6 x 3 x 3 mm  |

## DETOOLZ SMART WORK

Mobile: 0374.496.580 www.micul-fermier.ro contact@micul-fermier.ro

## DETOOLZ SMART WORK

Mobile: 0374.496.580 www.micul-fermier.ro contact@micul-fermier.ro